





## Computer Cable, 20-ft. IEEE 1284 AB Parallel Gold Cable Cen36M to DB25M

MODEL NUMBER: P606-020



#### Description

Tripp Lite's 20-ft. IEEE 1284 A-B gold parallel printer cable connects computers with a DB25 female parallel port to parallel printers with a Centronics 36 female parallel port. It supports high-speed IEEE 1284 bi-directional communication. The cable features gold plated DB25 male/Cent36 male connectors and gold plated copper contacts for superior conductivity. It is manufactured from superior molded cable with integral strain relief and double shielding for maximum EMI/RFI protection. It contains lowcapacitance, impedance matched, twisted-pair conductors that protect against cross-talk and other transmission problems. Tripp Lite warrants this product to be free from defects in materials and workmanship for life.

### **Features**

- Supports high-speed IEEE 1284 bi-directional communication (modes: standard compatible nibble byte ECP and EPP)
- Length: 20-ft. Connectors: DB25 male/Cent36 male
- · Gold plated connectors and gold plated copper contacts offer superior conductivity
- Superior molded cable with integral strain relief and double shielding (foil and braid) for maximum EMI/RFI protection
- · Low-capacitance impedance matched twisted-pair conductors protect against cross-talk and other transmission problems
- · Bi-directional communication allows your printer to broadcast printer error messages back to network computers
- · Molded ends with easy-grip textured overmold
- Tripp Lite warrants this product to be free from defects in materials and workmanship for life

# **Specifications**

### **Highlights**

- Superior molded cables with integral strain relief and foilshielding for maximum EMI/RFI protection
- IEEE 1284 cables' gold-plated connectors provide superior conductivity and support highspeed bi-directional printing

### **System Requirements**

- Computers with a DB25 Female parallel port
- · Parallel printers with a Centronics 36 Female parallel port with high-speed IEEE 1284 Bi-Directional communication (although not essential).

### Package Includes

• 20-ft. IEEE 1284 AB Parallel Gold Cable Cen36M to DB25M





OVERVIEW	
UPC Code	037332013583
OPC Code	037332013363
INPUT	
Cable Length (ft.)	20
Cable Length (m)	6.10
PHYSICAL	
Shipping Dimensions (hwd / in.)	12.75 x 10.00 x 1.25
Shipping Dimensions (hwd / cm)	32.38 x 25.40 x 3.18
Shipping Weight (lbs.)	1.50
Shipping Weight (kg)	0.68
CONNECTIONS	
Side A - Connector 1	DB25 (MALE)
Side B - Connector 1	CENTRONICS 36 (MALE)
WARRANTY	
Product Warranty Period (Worldwide)	Lifetime limited warranty

© 2019 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <a href="https://www.tripplite.com/products/product-certification-agencies">https://www.tripplite.com/products/product-certification-agencies</a>