



NOTES:

MATERIAL: HOUSING: SHELL: CONTACT:

THERMOPLASTIC POLYESTER, UL94V-0 STEEL, NICKEL PLATED COPPER ALLOY, GOLD FLASH PLATING

(1)

OPERATING TEMPERATURE: -55°C TO +125°C

CURRENT RATING:3A PER CONTACTCONTACT RESISTANCE:25mΩ MAX.INSULATOR RESISTANCE:5000MΩ min.DIELECTRICWITHSTANDING VOLTAGE:100V AC rms

	SW REFERENCE NO.: 622 ASSEMBLY		
	DRAWN: C.B	DATE: AUG. 01/2018	
	CHECKED:	DATE:	
	SCALE: (IN C.A.D. 1:1)	SHEET 1 OF	1
	DRAWING NUMBER: 622-025-2	622-025-260-542	
	PART NUMBER: 622-025-260-542		1



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.



622 SERIES D-SUB CONNECTOR

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.