









10.70 5.80

.XX ±0.13

.XXX ±0.05

Ν	О	ΤI	E	S	:

MATERIAL: HOUSING: SHELL: CONTACT:	THERMOPLASTIC POLYESTE STEEL, NICKEL PLATED COPPER ALLOY, 30µ GOLD F	
OPERATING TEMPERATURE:	-55°C ~ 125°C	
POWER/CO-AX CONTACT RATING: (IF PRESENT)	75Ω (IMPEDANCE)	
SIGNAL CONTACT CURRENT RATING: SIGNAL CONTACT RESISTANCE:	5A PER CONTACT 10mΩ MAX.	
INSULATOR RESISTANCE: DIELECTRIC	5000MΩ min.	* 000 * 000
WITHSTANDING VOLTAGE:	1000V AC rms	

	Ű		
000	000		
	<u> </u>	℣℗ℾ	
	-		

	COMBINATION D-SUB		SW REFERENCE NO.: 630 COMBO ASSEMBLY			
			DRAWN: C.B	DATE: JAN. 01/20	19	
			CHECKED:	DATE:		
	EDAC INC	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INCAND	SCALE: (IN C.A.D. 1:1)	SHEET 1 OF	2	
YOUR CO	TORONTO, ONTARIO CANADA	SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	DRAWING NUMBER: 630-11W	1640-7N1	ISSUE	
	YOUR CONNECTION TO QUALITY & SERVICE		PART NUMBER: 630-11W	1640-7N1	1	



11.94

THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

