



.XX ±0.13

.XXX ±0.05




ISSUE NUMBER ORIGINAL






## NOTES:

MATERIAL: HOUSING: SHELL: CONTACT:	THERMOPLASTIC POLYESTER, UL94V-0 STEEL, TIN PLATED COPPER ALLOY, GOLD FLASH PLATED	
OPERATING TEMPERATURE:	-55°C ~ 125°C	
POWER/CO-AX CONTACT RATING: (IF PRESENT) SIGNAL CONTACT CURRENT RATING:	20A (CURRENT)	
SIGNAL CONTACT CORRENT RATING: SIGNAL CONTACT RESISTANCE:	$10m\Omega$ MAX.	1
INSULATOR RESISTANCE: DIELECTRIC	5000MΩ min.	) _
WITHSTANDING VOLTAGE:	1000V AC rms	



			SW REFERENCE NO.: 630 COMBO ASSEMBLY			
COMBINATION D-SUB		DRAWN: C.B		DATE: JAN. 01/2019		
			CHECKED	):	DATE:	
EDAC	EDAC INC	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	SCALE:	(IN C.A.D. 1:1)	SHEET 1 OF	2
	ADA		DRAWING NUMBER: 630-7W2-2		-250-2TA	ISSUE
YOUR CONNECTION TO QUALITY & S			PART NUI	MBER: 630-7W2-	-250-2TA	1



J COMPLIANT

