



Product: 6502FE ☑

Security & Alarm Cable, Plenum-CMP, 4-22 AWG stranded bare copper conductors with Flamarrest® insulation, Beldfoil® shield and Flamarrest® jacket with ripcord

## **Product Description**

Security & Sound Cable, Plenum-CMP, 4-22 AWG stranded bare copper conductors with Flamarrest® insulation, Beldfoil® shield and Flamarrest® jacket with ripcord

## **Technical Specifications**

Suitable Appl	cations:	Security S	ystem, Interc	om/PA, Audio/Speaker, Po	wer-Limited Controls, Noisy En
Construction Details					
Conductor					
Element	Number of Element	Size	Stranding	Material	
Conductor(s)	4	22 AWG	7x30	BC - Bare Copper	
Insulation					
Element	Material	Non	n. Thickness	Nom. Insulation Diame	ter Color Code
Conductor(s)	PVC Polyvinyl Chlo	-:			
Conductor(3)	F VC - Folyvillyl Cilic	ride 0.008	9 in (0.23 mm	0.047 in (1.2 mm)	Black, Red, White, Green
. ,	FVC - Follyvillyl Clilic	nde 0.008	9 in (0.23 mm	0.047 in (1.2 mm)	Black, Red, White, Green
Outer Shield			· ·	,	Black, Red, White, Green
Outer Shield Shield Type	Material	Cove	erage Drai	inwire Type	Black, Red, White, Green
Outer Shield Shield Type Tape		Cove	erage Drai	,	Black, Red, White, Green
Outer Shield Shield Type Tape	Material	Cove	erage Drai	inwire Type	Black, Red, White, Green
Outer Shield Shield Type Tape	Material Bi-Laminate (Alum+F	Cove	erage Drai	inwire Type VG (7x32) TC	Black, Red, White, Green
Outer Shield Shield Type Tape Outer Jacket Mater	Material Bi-Laminate (Alum+F	Coverage of the control of the contr	Prage Drain 24 AV	inwire Type VG (7x32) TC	Black, Red, White, Green
Outer Shield Shield Type Tape Outer Jacket Mate PVC - Polyvir	Material Bi-Laminate (Alum+F	Coverage of the control of the contr	Prage Drain	inwire Type VG (7x32) TC	Black, Red, White, Green
Outer Shield Shield Type Tape Outer Jacket Matei PVC - Polyvir Overall Cable	Material  Bi-Laminate (Alum+F  ial Nom. Tr  yl Chloride 0.015 in (	Coverage of the control of the contr	Prage Drain	inwire Type VG (7x32) TC	Black, Red, White, Green

Element	Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Nom. Capacitance Cond-to-Other (Conds + Shield)	Max. Current
Conductor(s)	16.2 Ohm/1000ft	33.0 pF/ft (108 pF/m)	59 pF/ft (190 pF/m)	2.2 Amps per Conductor at 25°C

# Voltage

UL Voltage Rating 300 V (CMP)

### **Mechanical Characteristics**

## Temperature

UL Temperature	Operating
75°C	0°C to +75°C

### Bend Radius

Stationary Min.	Installation Min.
1.47 in (37.3 mm)	1.47 in (37.3 mm)

Max. Pull Tension:	42 lbs (19 kg)
Bulk Cable Weight:	17 lbs/1000ft

### **Standards and Compliance**

Environmental Suitability:	Indoor - Plenum, Indoor
Flammability / Reaction to Fire:	NFPA 262, UL 910 (Plenum), FT6
CPR Compliance:	CPR Euroclass: Eca
NEC / UL Compliance:	Article 800, CMP
CEC / C(UL) Compliance:	CMP
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
UK Regulation Compliance:	UKCA Mark
APAC Compliance:	China RoHS II (GB/T 26572-2011)
Non-Plenum Number:	5502FE

#### **History**

U	pdate and Revision:	Revision Number: 0.474 Revision Date: 04-03-2023	1
---	---------------------	--	---

## **Part Numbers**

#### Variants

Item #	Color	UPC
6502FE 8771000	Natural	612825177609
6502FE 877500	Natural	612825177616
6502FE 877C500	Natural	
6502FE 877U1000	Natural	612825177593
6502FE 0071000	Violet	612825377726
6502FE 0071000	Violet	612825377726
6502FE 007U1000	Violet	612825377832
6502FE 007U1000	Violet	612825377832

### © 2023 Belden, Inc

### All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.