



NOTES: Finish (Plating Thickness in Micro-inches)
 1. Brass
 2. Nickel Pl. 100 Min. Thick over Copper Pl. 50 Min. Thick
 3. Gold Pl. 3 Min Thick over Nickel Pl. 50 Min. Thick over Copper Pl. 50 Min. Thick
 4. Teflon

RoHS Compliant

Crimped Ferrule
 Hex Crimp Size .213 (5.41)

| | | | | | Dimensions are in Inches | | | | Part No. | | NTE Electronics | |
|---|---------------|-------------|----------|--------|---------------------------------------|-------------|-------|-----|----------|---|--|--|
| | | | | | Unless Otherwise Specified Tolerances | | | | Approved | | | |
| 7 | Ferrule | Copper | Note 2 | 1 | | | | | Date | | SMA Crimp Plug (For RG-58, 58A, 58C, 141, LMR195) | |
| 6 | Contact Pin | Note 1 | Note 3 | 1 | | | | | 6-9-2011 | | | |
| 5 | Gasket | Silicone | Red | 1 | | | | | Checked | | Drawing No. 06-S005 | |
| 4 | Retainer Ring | SUS 303 | Natural | 1 | | | | | Date | | | |
| 3 | Insulator | Note 4 | Natural | 1 | | | | | Date | | File No. | |
| 2 | Body | Note 1 | Note 2 | 1 | | | | | 6-9-2011 | | | |
| 1 | Shell | Note 1 | Note 2 | 1 | | | | | Date | | | |
| | No | Description | Material | Finish | Q'ty | Drawing No. | Scale | 4/1 | Issue | A | | |