

Data sheet | Item number: 706-100/550-300

Connection cable; 50-pole; with solder pin; Male connector; open-ended;
Length: 3 m; Conductor cross-section: 0.25 mm²



www.wago.com/706-100/550-300



i Picture differs from the item.

Color coding acc. to DIN VDE 47 100		50 poles male Sub-D connector
		Pin number
White		1
Brown		2
Green		3
Yellow		4
Grey		5
Pink		6
Blue		7
Red		8
Black		9
Violet		10
Grey-Pink		11
Red-Blue		12
White-Green		13
Brown-Green		14
White-Yellow		15
Yellow-Brown		16
White-Grey		17
Grey-Brown		18
White-Pink		19
Pink-Brown		20
White-Blue		21
Brown-Blue		22
White-Red		23
Brown-Red		24
White-Black		25
Brown-Black		26
Grey-Green		27
Yellow-Grey		28
Pink-Green		29
Yellow-Pink		30
Green-Blue		31
Yellow-Blue		32
Green-Red		33
Yellow-Red		34
Green-Black		35
Yellow-Black		36
Grey-Blue		37
Pink-Blue		38
Grey-Red		39
Pink-Red		40
Grey-Black		41
Pink-Black		42
Blue-Black		43
Red-Black		44
White-Brown-Black		45
Yellow-Green-Black		46
Grey-Pink-Black		47
Red-Blue-Black		48
White-Green-Black		49
Brown-Green-Black		50
Shield		Connected to Sub-D

Data
Notes

Note When using more than 10 wires, the maximum current per wire must be reduced to 1 A.

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



Electrical data

Operating voltage	≤ AC/DC 35 V
Current per wire (max.)	2 A

Connection data

Cable type	LiYCY
Color code	per DIN VDE 47100

Connection 1

Connector	D-subminiature male connector
Pole number 1	50
Connection type 1	System
Wire cross-section	0.25 mm ²
Connection type	D-subminiature

Connection 2

Connector 2	open-ended
Connection type 2	open-ended

Physical data

Cable length	3 m
--------------	-----

Material Data

Weight	1449 g
--------	--------

Environmental requirements

Ambient temperature (operation)	-20 ... +50 °C
---------------------------------	----------------

Commercial data

ETIM 8.0	EC001855
ETIM 7.0	EC001855
PU (SPU)	1 pcs
Packaging type	bag
Country of origin	FR

Subject to changes. Please also observe the further product documentation!



GTIN	4055143976626
------	---------------

Customs tariff number	85444290900
-----------------------	-------------

Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 706-100/550-300	URL	Download
Connection cable; 50-pole; with solder pin; Male connector; open-ended; Length: 3 m; Conductor cross-section: 0.25 mm ²		

Installation Notes

Subject to changes. Please also observe the further product documentation!