MG Chemicals (Head Office)

Surrey, British Columbia V4N 4E7

9347-193 Street

CANADA





834B-A

(PART A)

Safety Data Sheet

Section 1: Identification

Product Identifier and Other Means of Identification

Product Identifier: 834B-A

Other Product Identifier: Black Flame Retardant Epoxy

Related Part # 834B-375ML, 834B-2.7L, 834B-10.8L, 834B-60L

Recommended Use and Restriction on Use

Use: Resin for use with epoxy hardener

Uses Advised Against: Not for use as spray coating

Details of Manufacturer or Importer

Manufacturer

MG Chemicals 1210 Corporate Drive Burlington, Ontario L7L 5R6 CANADA

 ★
 +1-800-340-0772
 ★
 +1-905-331-1396

 FAX
 +1-800-340-0773
 FAX
 +1-905-331-2682

 E-MAIL
 support@mgchemicals.com
 E-MAIL
 info@mgchemicals.com

WEB <u>www.mgchemicals.com</u>

E-MAIL (Competent Person): sds@mgchemicals.com

Emergency Phone Number

For hazardous material incidents ONLY (leaks, spills, fires, exposures or accidents) USA or CANADA—Call Verisk 3E at +1-866-519-4752 or +1-760-476-3962 (Service access code: 335388)

For emergencies involving the transport of dangerous goods; 24/7 service CANADA—Call CANUTEC collect at +1-613-996-6666 or *666 on cellular phones

Burlington, Ontario, Canada

834B-A

(PART A)

Section 2: Hazard(s) Identification

Classification of the Chemical Material

GHS Categories

Criteria		Category	Signal Word	Pictograms
Sensitization	Skin	1	Warning	Exclamation
Skin Irritation		2	Warning	Exclamation
Eye Irritation		2	Warning	Exclamation
Reproductive Toxicity	Oral	2	Warning	Health
Hazardous to the Aquatic Environment	Chronic	2	none	Environment

Note: The degree of severity is ranked within each hazard class from 1 (Highest Severity) to up to 5 (Lowest Severity), which is opposite to HMIS and NFPA conventions. Severity category rankings do not allow comparisons between classes.

Label Elements

Signal Word	WARNING
Pictograms	Hazard Statements
	H317: May cause an allergic skin reaction
	H315: Causes skin irritation
	H319: Causes serious eye irritation
	H361: Suspected of damaging fertility or the unborn child
***	H411: Toxic to aquatic life with long lasting effects

Section continued on the next page

Page 2 of 16



SAI Global File #004008 Burlington, Ontario, Canada

834B-A (PART A)

Continued...

Prevention	Precautionary Statements
P102	Keep out of reach of children.
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P261	Avoid breathing fumes/vapors.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P264	Wash hands thoroughly after handling.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
Response	Precautionary Statements
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P302 + P352	IF ON SKIN: Wash with plenty water.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P308 + P313	IF exposed or concerned: Get medical advice/attention.
P391	Collect spillage.
Storage	Precautionary Statements
P405	Store locked up.
Disposal	Precautionary Statements
P501	Dispose of contents/container in accordance to local/regional/international regulations.

Hazards Not Otherwise Classified

Other Criteria	Hazard Statements/Precautionary Statement	Signal Word	Pictograms
None	None	None	None

Burlington, Ontario, Canada

(PART A)

834B-A

Section 3: Composition/Information on Ingredients

CAS #	Chemical Name	%(weight)
25085-99-8	bisphenol-A-(epichlorhydrin)	30%
21645-51-2	aluminum trihydrate	21%
68333-79-9	ammonium polyphosphate	19%
1344-28-1	aluminum oxide	16%
17557-23-2	neopentyl glycol diglycidyl ether	6%
138265-88-0	zinc borate	5%
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin)	1%
1333-86-4	carbon black	0.4%

Section 4: First-Aid Measures

Exposure Condition	GHS Code: Precautionary Statement
IF IN EYES	P305 + P351 + P338
Immediate Symptoms	redness, irritation, pain
Response	Rinse cautiously with water for at least 20 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
IF ON SKIN	P302 + P352, P333 + P313, P362 + P364
Immediate Symptoms	redness, irritation, dry skin, allergic contact dermatitis
Response	Wash with plenty of water.
	If skin irritation or rash occurs: Get medical advice/attention.
	Take off contaminated clothing and wash it before reuse.
IF INHALED	P304 + P340
Immediate Symptoms	cough, irritation of the respiratory track
Response	Remove person to fresh air and keep comfortable for breathing.
IF SWALLOWED	P301 + P330, P331, P308 + P313
Immediate Symptoms	nausea, vomiting, diarrhea, burns or irritation to the digestive tract
Response	Rinse mouth. Do not induce vomiting.
	IF exposed or concerned: Get medical advice/attention.

SAI Global File #004008 Burlington, Ontario, Canada

834B-A (PART A)

Section 5: Fire-Fighting Measures

Extinguishing Media In case of fire: Use extinguishing media suitable for surrounding

materials.

Specific Hazards Not flammable or combustible, but will burn if involved in a fire.

Produces irritating smoke of unknown toxicity in fires.

Prevent fire-fighting wash from entering waterway or sewer

system.

Combustion Products Produces carbon oxides (CO, CO₂), zinc oxides, boron oxides,

ammonia and other toxic fumes.

Fire-Fighter Wear self-contained breathing apparatus and full fire-fighting

turn-out gear.

Section 6: Accidental Release Measures

Personal Protection See personal protection recommendations in Section 8.

Precautions for

Avoid breathing the fumes/vapors. Remove or keep away all sources of extreme heat or open flames.

Response

sources of extreme heat of open hames.

Environmental Precautions

Avoid releasing to the environment. Prevent spill from entering

drains and waterways.

Containment Methods

Contain with inert and non-flammable absorbent (such as soil,

sand, vermiculite).

Cleaning Methods

Collect liquid in a sealable, solvent-resistant container. Sprinkle inert absorbent compound onto spill, then sweep into the container. Wash spill area with soap and water to remove the

last traces of residue.

Disposal Methods

Dispose of spill waste according to Section 13.

SAI Global File #004008 Burlington, Ontario, Canada

834B-A (PART A)

Section 7: Handling and Storage

Prevention Keep out of reach of children.

Obtain special instructions before use. Do not handle until all

safety precautions have been read and understood.

Contaminated work clothing should not be allowed out of the

workplace.

Avoid breathing fumes/vapors.

Avoid release to the environment.

Handling Wear protective gloves/protective clothing/eye protection/face

protection.

Take off contaminated clothing and wash it before reuse.

Wash hands thoroughly after handling.

Collect spillage.

Storage Store locked up.

Section 8: Exposure Controls/Personal Protection

Substances with Occupational Exposure Limit Values

Chemical Name	Country or Vendor	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
aluminum metal	ACGIH	1 mg/m ³	Not established
and insoluble	U.S.A. OSHA PEL	15 mg/m ³	Not established
compounds ^{a)}	Canada AB	10 mg/m ³	Not established
	Canada BC	1 mg/m ³	Not established
	Canada ON	1 mg/m³	Not established
	Canada QC	10 mg/m ³	Not established

Section continued on the next page

SAI Global File #004008 Burlington, Ontario, Canada

834B-A (PART A)

Continued...

Chemical Name	Country or Vendor	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
aluminium oxide	ACGIH	Not established	Not established
	U.S.A. OSHA PEL	5 mg/m ³	Not established
	Canada AB	10 mg/m ³	Not established
	Canada BC	Not established	Not established
	Canada ON	Not established	Not established
	Canada QC	10 mg/m ³	Not established
carbon black ^{a)}	ACGIH	3.5 mg/m ³	Not established
	U.S.A. OSHA PEL	3.5 mg/m ³	Not established
	Canada AB	3.5 mg/m ³	Not established
	Canada BC	3 mg/m ³	Not established
	Canada ON	3.5 mg/m ³	Not established
	Canada QC	3.5 mg/m ³	Not established

Note: Ingredients are listed in descending weight contribution order (from greatest to least). The ACGIH¹, OSHA (Table Z-1), and Canadian provinces exposure limits were consulted. Limits from the RTECS database² and from suppliers' SDS were also consulted. Short term exposure limits (STEL) are for 15 min and long term permissible exposure limits (PEL) for 8 h.

a) Respirable airborne particles

Engineering Controls

Ventilation

Keep airborne concentrations below the occupational exposure

limits (OEL).

Because the carbon black is bound to the liquid mixture, it does not present an airborne hazard under normal use. Ensure adequate ventilation if the product is mechanically misted or aerosolized.

Personal Protective Equipment

Eye protection Wear appropriate protective eyeglasses or chemical safety

goggles.

RECOMMENDATION: Use safety glasses with lateral protection

(side shields).

Skin Protection Wear appropriate protective clothing to prevent skin contact.

RECOMMENDATION: Use butyl rubber, neoprene, or other

chemically resistant gloves.

Section continued on the next page

Page **7** of **16**

SAI Global File #004008 Burlington, Ontario, Canada

834B-A (*Part A*)

Respiratory Protection

If the product is heated or worker has a known allergic reaction, consider using a full mask with organic vapor cartridge or with an independent air supply.

Generally, for emergencies and exposure above 0.5 mg/m³, use a self-contained breathing apparatus with full face piece operated in a pressure positive mode.

RECOMMENDATION: Consult your local safety supply store to ensure that your respirator has a NIOSH (U.S.) approved filter cartridges appropriate for the ingredients listed in Section 3. The respirator should be fitted to the employee by a professional. Ensure vapor cartridges are stored in sealed plastic bags when not being used.

General Hygiene Considerations

Wash hands thoroughly with water and soap after handling.

Section 9: Physical and Chemical Properties

Physical State	Liquid	Lower Flammability Limit	Not available
Appearance	Black	Upper Flammability Limit	Not available
Odor	Mild	Vapor Pressure @25°C	Not available
Odor Threshold	Not available	Vapor Density	Not available
рН	Not available	Relative Density @25 °C	1.69
Freezing/Melting Point	Not available	Solubility in Water	Practically insoluble
Initial Boiling Point	Not available	Partition Coefficient n-octanol/water	Not available
Flash Point	Not available	Auto-ignition Temperature	Not available
Evaporation Rate	Not available	Decomposition Temperature	Not available
Flammability	Non Flammable	Viscosity @25 °C	27 500 cP [16 300 mm ² /s]



SAI Global File #004008 Burlington, Ontario, Canada

834B-A (PART A)

Section 10: Stability and Reactivity

Reactivity Reacts exothermically with amines.

Chemical Stability Chemically stable at normal temperatures and pressures.

Conditions to

Excessive heat, and incompatible substances. Do not use in a way

Avoid that forms a mist or aerosolize the product.

Incompatibilities Strong oxidizing agents, strong acids, and strong bases.

Polymerization Will not occur

Decomposition Will not decompose under normal conditions. For thermal

decomposition, see combustion products in Section 5.

Section 11: Toxicological Information

Summary of Effects and Symptoms by Routes of Exposure

Eyes May cause severe eye irritation, redness, and pain.

Skin May cause redness, dry skin, serious skin irritation, and skin sensitization.

Inhalation May cause cough, and irritation of the respiratory system.

Ingestion It may cause nausea, vomiting, diarrhea, burns or irritation to the

digestive tract.

Chronic Prolonged and repeated exposure may lead to skin sensitization reactions.

Long term exposure to carbon black dust or mist may cause cancer.

Lethal Exposure Concentrations

Chemical Name	LD50	LD50	LC50
	oral	dermal	inhalation
bisphenol-A-(epichlorhydrin)	>2 000 mg/kg	23 000 mg/kg	Not
	Rat	Rabbit	available
aluminum trihydrate	79 000 mg/kg	Not	Not
	Rat	available	available
ammonium polyphosphate	300 mg/kg	Not	Not
	Rat	available	available
aluminum oxide	Not	Not	Not
	available	available	available

Section continued on the next page

Page **9** of **16**



SAI Global File #004008 Burlington, Ontario, Canada

834B-A (PART A)

Continued...

Chemical Name	LD50	LD50	LC50
	oral	dermal	inhalation
neopentyl glycol diglycidyl ether	Not	Not	Not
	available	available	available
zinc borate	10 000 mg/kg	10 000 mg/kg	Not
	Rat	Rat	available
reaction product: bisphenol-A-	>2 000 mg/kg	>2 000 mg/kg	Not
(epichlorhydrin)	Rat	Rat	available
carbon black	>15 g/kg	>3 g/kg	Not
	Rat	Rabbit	available

Note: Toxicity data from the RTECS² and ECHA databases were consulted. The data from supplier SDSs were also consulted.

Other Toxicological Effects

Skin corrosion/irritation	Causes skin irritation.
----------------------------------	-------------------------

Serious eye damage/irritation Causes serious irritation.

Respiratory and skin The epoxy resin components (CAS# 25085-99-8, and **sensitization** (allergic reactions) 25068-38-6) may cause skin sensitization in humans.

Carcinogenicity The carbon black is possibly carcinogenic by airborne routes of exposures. Because they are both bound in (risk of cancer)

the epoxy liquid mixture, it is not expected to be available as an airborne hazard (dust, mist, or spray)

under normal use.

Carbon Black [1333-86-4]

IARC Group 2B: Possibly carcinogenic to humans ACGIH A4: Not classified as a human carcinogen CA Prop 65: Listed as a carcinogen (airborne, as

Animal ingestion studies show that high doses of zinc

unbound particles of respirable size)

NTP: Not listed

Mutagenicity

Based on available data, the classification criteria are (risk of heritable genetic effects) not met.

Reproductive Toxicity

(risk to sex functions) borate cause reproductive and developmental effects.

Teratogenicity

Based on available data, the classification criteria are (risk of fetus malformation) not met.

Section continued on the next page

Page 10 of 16



SAI Global File #004008 Burlington, Ontario, Canada

834B-A (PART A)

STOT-single exposure Based on available data, the classification criteria are

not met.

STOT-repeated exposure Based on available data, the classification criteria are

not met.

Aspiration hazardBased on available data, the classification criteria are

not met. The kinematic viscosity is >20.5 mm²/s at

40 °C.

Section 12: Ecological Information

Ecological classifications are based on the IMDG/GHS criteria in conjunction with ecotoxicological data from our suppliers, the European Chemical Agency database (http://echa.europa.eu), and other reliable sources.

The epoxy resins (CAS# 25085-99-8, and 25068-38-6) have a LC50 for

aquatic organisms 1 mg/L to 10 mg/L.

The zinc borate is classified as a chronic category 1 environmental toxicant with a M-Factor of 1 (with minimal LC50 96 h of 2.4 mg/L for Oncorhhynchus mykiss (rainbow trout); LC50 48 h of 76 mg/L Daphnia magna (water flea); and transformation/dissolution endpoint for zinc borate powder that release of 0.452 mg/L of zinc ion, which is higher than zinc's NOEC limit).

Based on available data, ammonium polyphosphate, aluminum trihyrate, aluminum oxide, neopentyl glycol diglycidyl ether and carbon black are not classified as environmental hazards according to GHS criteria.

Acute Ecotoxicity

Available toxicity data does not meet classification thresholds.

Chronic Ecotoxicity

Category 2

Toxic to aquatic life with long lasting effects

Avoid release to the environment. Collect spillage.

Biodegradability

Not available

Bioaccumulation

Not available



SAI Global File #004008 Burlington, Ontario, Canada

834B-A

(PART A)

Section 13: Disposal Considerations

Dispose of contents in accordance with all local, regional, national, and international regulations.

Section 14: Transport Information

Ground

Refer to TDG regulations (Canadian Transportation of Dangerous Goods regulations); **USA DOT 49 CFR** (Parts 100 to 185) **Regulations.**

Sizes under 450 L Part A of all 834B kits

NOT REGULATED in TDG per Special Provisions 99

Sizes 5 L and under Part A of 834B-375ML, 834B-2.7L kits

NOT REGULATED in 49 CFR per exception 171.4 (c)(2)

49 CFR: Sizes greater than 5 L Part A of 834B-10.8L, 834B-60L kits

UN number: UN3082 Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,N.O.S. (Reaction product: bisphenol-A-(epichlorhydrin))

Class: 9

Packing Group: III

Marine Pollutant: Yes



Special Provision 99 (2): These Regulations, except for Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases) and Part 2 (Classification), do not apply to the handling, offering for transport or transporting of less than 450 kg of UN3077, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S., or less than 450 L of UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., on a road vehicle or a railway vehicle. The dangerous goods must be contained in one or more small means of containment designed, constructed, filled, closed, secured and maintained so that under normal conditions of transport, including handling, there will be no accidental release of the dangerous goods that could endanger public safety.

Section continued on the next page

Page 12 of 16



SAI Global File #004008 Burlington, Ontario, Canada

834B-A (PART A)

Air

Refer to ICAO-IATA Dangerous Goods Regulations.

Sizes 5 L and under: Part A of 834B-375ML/2.7L kits

NOT REGULATEDNot Restricted, as per
Special Provisions **A197**

Sizes greater than 5 L: Part A of 834B-10.8L, 834B-60L kit

UN number: UN3082 Shipping Name:

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Reaction product: bisphenol-A-

(epichlorhydrin))

Class: 9

Packing Group: III Marine Pollutant: Yes



Special Provision A197: These substances when transported in single or combination packagings containing net quantity per single or inner packaging of less than 5 L or less for liquids or having a net mass of 5 kg or less for solids, are not subject to any other provisions of these Regulations provided the packagings meet the general provisions 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

Sea

Refer to IMDG regulations.

Sizes 5 L and under: Part A of 834B-375ML/3L kits NOT REGULATED

per 2.10.2.7

Sizes greater than 5 L: Part A of 834B-60L kit
UN number: UN3082

Shipping Name:

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Reaction product: bisphenol-A-

(epichlorhydrin))

Class: 9

Packing Group: III Marine Pollutant: Yes



2.10.2.7: Marine pollutants packaged in single or combination packagings containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids are not subject to any other provision of this Code relevant to marine pollutants provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. In the case of marine pollutants also meeting the criteria for inclusion in another hazard class, all provisions of this Code relevant to any additional hazards continue to apply.

Note: Shipper must be appropriately <u>trained and certified</u> before involvement with the transport of dangerous goods.

Page **13** of **16**

SAI Global File #004008 Burlington, Ontario, Canada

834B-A (PART A)

Section 15: Regulatory Information

Canada

Domestic Substance List (DSL)/Non-Domestic Substance Lists (NDSL)

All hazardous ingredients are listed on the DSL/NDSL.

Hazardous Products Act (R.S.C., 1985, c. H-3)

The safety data sheet and label comply with the Hazardous Product Act and WHMIS 2015.

USA

Other Classifications

HMIS® RATING

HEALTH: * 3 FLAMMABILITY: 1 PHYSICAL HAZARD: 0 PERSONAL PROTECTION:

NFPA® 704 CODES



Approximate HMIS and NFPA Risk Ratings Legend:

0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

CAA (Clean Air Act, USA)

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

EPCRA (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45

This product does not contain ingredients that are subject to the reporting requirements of section 313 Title III of the SARA of 1986 and 40 CFR part 372.

TSCA (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

California Proposition 65 (Chemicals known to cause cancer or reproductive toxicity, USA).

This product contains carbon black, but it is bound and exposures during normal conditions of uses are below the Safe Harbor Threshold.

Section continued on the next page

Page **14** of **16**



SAI Global File #004008 Burlington, Ontario, Canada

834B-A (PART A)

Europe

RoHS (Restriction of Hazardous Substances Directive)

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, PBDE's, DEHP, BBP, DBP, or DIBP and complies with European RoHS regulations.

WEEE (Waste Electrical and Electronic Equipment Directive)

This product is not a piece of electrical or electronics equipment, and is therefore not governed by this regulation.

Section 16: Other Information

MSDS Prepared by MG Chemicals' Regulatory Department

Date of Revision 02 March 2020 Supersedes 12 October 2017

Reason for Changes: Update to the emergency phone number information.

Reference

- 1) ACGIH 2017 TLVs and BEIs: Based on the documentation of the threshold limit values for chemical substances and physical agents & biological exposure indices, American Conference of Governmental of Industrial Hygienist Cincinnati, OH (2017).
- 2) All toxicological data were checked against the RTECS (Registry of Toxic Effects of Chemical Substances®)

Abbreviations

American Conference of Governmental Industrial Hygienists (USA)
Half maximal effective concentration
Half maximal effective loading
No observable effect loading ratio
Globally Harmonized System of Classification of Labeling of Chemicals
Lethal Concentration 50%
Lowest published lethal concentration
Lethal Dose 50%
Permissible Exposure Limit
Short-Term Exposure Limit
Lowest published toxic concentration
Time Weighted Average
Volatile Organic Content

Section continued on the next page

Page **15** of **16**



SAI Global File #004008 Burlington, Ontario, Canada

834B-A (PART A)

Technical Queries Contact us regarding any questions, improvement suggestions, or

problems with this product. Application notes, instructions, and FAQs

are located at www.mgchemicals.com.

Email: support@mgchemicals.com

Mailing Addresses Manufacturing & Support Head Office

1210 Corporate Drive 9347–193rd Street

Burlington, Ontario, Canada Surrey, British Columbia, Canada

L7L 5R6 V4N 4E7

Disclaimer This safety data sheet is provided as an information resource only.

M.G. Chemicals, Ltd. believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to query and verify any information seeming suspect where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, regional,

national, and international regulations.