[	⊂			0		A	
4	Z T T T T T T T T T T T T T						4
				LAYOUT SH	OWN AS EXAMPLE		
		Keying Shown as example					
	CHARACTERISTICS	Connector dimension Dim Nominal	]				
N	-Standard : Based on MIL-DTL-38999 Series III         -Shell Material       : Aluminium         -Shell Plating       : Nickel         -Insulator       : Thermoplastic         -Contacts       : Copper Alloy         -Seals & Grommet       : Silicon Elastomer	ØS 41.7 Max Z 31 Max VV THREAD M31x1-6g		due to a use of the P the Specifications issued		with hird party	2
	<ul> <li>-Contact Plating : Gold over copper Alloy 0.8μm minimum</li> <li>-Durability : 500 Mating cycles</li> <li>-Delivered with Souriau contacts and Accessories</li> </ul>			PN: 8	D521F41BC		2
	-Temperature Range <u>-</u> -65°C to +200°C -Salt Spray : 48 hours		A	06-10-2016 First Release			
_	-Mass : 60.18 g ± 10%		ISS Designe	DATE Latest modification - by bd By: Date:	CU	MOD N STOMER DRAWING	<u>N°</u>
				TITLE	Aluminium Plug 8D se	eries	
<u> </u>	BASIC SERIES: 8D 5 - 21 F 4 SHELL TYPE : Plug with RFI Shielding	41 B C	SCA NA	Tol	eral linear erances: ±	NPRDS / PROJECT 859	1
	CONTACT TYPE     : Standard Crimp Contact       SHELL SIZE : 21     CONTACT TYPE : SOCKET(500 Mage)			- SOURIAU WWW.SOURIAU.COIVI it must not be reproduced or			
	PLATING : F = Nickel	CONTACT LAYO		300	JRIAU DRG N°	SHEET	
	H G	F E		2   8L	D521F41BC-C	1/2	

	Ŧ	۵	г	m	D	<b>O</b>	
		Contact Layout					
4		T HOLES					
	<	31° 23' 41'					
		We we we					
	Shell Arrangement Numt size no. cont	Insert arrangement 21-41 per of Size Service Contact Supersedes acts contacts rating location	-				
ω	21 -41 4	1 20 I All MS20055-41					
-	_						
						SOURIAU shall not be liable due to a use of the Produ	
						the Specifications issued by ei (professional recomn	
N							Count FR
						PN: 8D5	521
					A 06-10-20	16 First Release	
					ISS DATE		
					Designed By:	Date:	
					TITLE	Δ١	umir
					SCALE	General li Tolerand	
<u> </u>					NA		
					SOURIA	U WWW.SOURIA	۹U.C
						SOUR	IAU
		Γ	Ι		A3	8D52	21F
	Н	G	l F	I E	D	C	

