# **NSYS3D6525**

Spacial S3D plain door w/o mount.plate. H600xW500xD250.IP66 IK10 RAL7035.





#### Main

Spacial
Spacial S3D
Multi-purpose
Compact enclosure
23.62 in (600 mm)
19.69 in (500 mm)
9.84 in (250 mm)
Solid
Without mounting plate
Standard
Wall-mounting
1 body 1 door 1 lock 1 cable gland plate

#### Complementary

Complementary		
Body type	Gutter-shaped front rail double sheet thickness Single piece body	
Number of doors	Front face 1	
Door opening side	Reversible 120 °)	
Lock type	3 points lock, 3 mm double-bar	
Accessibility for operation	Front	
Removable parts	Door by hinges Cable gland plate by screws	
Material	steel	
Surface finish	Epoxy-polyester powder	
Color	Gray RAL 7035)	
Standards	IEC 62208	
Product Certifications	BV DNV CUL LR UL GL	
Net Weight	29.69 lb(US) (13.466 kg)	

### Environment

NEMA Degree of Protection	NEMA 4X/13	
IK degree of protection	IK10 IEC 62262	
IP degree of protection	IP66 IEC 60529	

## Ordering and shipping details

Category	80034-ENCLOSURE SYSTEMS WALL MOUNT METAL
Discount Schedule	ES1
GTIN	3606480159275
Nbr. of units in pkg.	1
Package weight(Lbs)	28.66 lb(US) (13.0 kg)
Returnability	No
Country of origin	FR

## Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	24.41 in (62 cm)	
Package 1 width	20.28 in (51.5 cm)	
Package 1 Length	11.81 in (30 cm)	

## Offer Sustainability

Green Premium product
REACh Declaration
Yes
Pro-active compliance (Product out of EU RoHS legal scope)
Yes
₫Yes
☐ China RoHS Declaration
Product Environmental Profile

## Contractual warranty

Warranty	18 months	