

Specification Sheet

Part Number: T30RA300HS



Cable Ties for AT2060, 30lb Tensile Strength, PA66HS, Black, 30/bandolier, 600/pkg

| | |
|--------------------------------|--|
| Article Number | 103-00003 |
| Type | T30RA |
| Color | Black (BK) |
| Features & Benefits | <ul style="list-style-type: none">• The AT2060 cable tie system is designed for automatic installation on bundles up to 1.25" and a minimum tensile strength of 30 lbs.• Available in reels of 3,000 each or bandoliers of 30 each. |
| Quantity Per | bag |
| Product Description | Includes AT2060 tool, power supply, power cord, tool cord, and maintenance and operation manual. |
| Short Description | Cable Ties for AT2060, 30lb Tensile Strength, PA66HS, Black, 30/bandolier, 600/pkg |

Global Part Name

T30RA-PA66HS-BK

Minimum Tensile Strength (Imperial)

30.0

Minimum Tensile Strength (Metric)

133.4

Length L (Imperial)

6.0

Length L (Metric)

152.4

Identification Plate Position

none

Reel Diameter (Imperial)

17.7

Reel Diameter (Metric)

450.0

Reel Width (Imperial)

7.197

Reel Width (Metric)

182.8

Voltage Range

27 Volt

Releasable Closure

No

Width W (Imperial)

0.14

Width W (Metric)

3.6

Bundle Diameter Min (Imperial)

0.06

Bundle Diameter Min (Metric)

1.5

Bundle Diameter Max (Imperial)

1.25

| | |
|---------------------------------------|--|
| Bundle Diameter Max (Metric) | 31.75 |
| Thickness T (Imperial) | 0.05 |
| Thickness T (Metric) | 1.2 |
| Cycle Time | 1.2 seconds |
| Power Supply | Electrical |
| Tension Force | Adjustable |
| Material | Polyamide 6.6 heat stabilized (PA66HS) |
| Material Shortcut | PA66HS |
| Flammability | UL 94 V2 |
| Operating Temperature (Metric) | -40°F to +275°F (-40°C to +135°C) |
| UL Recognized (US) | Yes |
| UL Recognized (US and Canada) | Yes |
| Package Quantity(Imperial) | 600 |
| Package Quantity (Metric) | 600 |
| Customs Number | 3926909988 |

Weight (Metric) 1.8

Weight (Imperial) 3.9

Reel Weight (Imperial) 7

Reel Weight (Metric) 3.175