


THIS SERIES FULLY CONFORMS TO

THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.






| N | 0 | ΓЕ | S: |
|---|---|----|----|
| | | | |

| MATERIAL: HOUSING: SHELL: CONTACT: | THERMOPLASTIC POLYESTER, UL94V-0 STEEL, NICKEL PLATED COPPER ALLOY, 30µ GOLD PLATED |
|--|---|
| OPERATING TEMPERATURE: | -55°C ~ 125°C |
| POWER/CO-AX CONTACT RATING: (IF PRESENT) | 30A (CURRENT) |
| SIGNAL CONTACT CURRENT RATING: SIGNAL CONTACT RESISTANCE: | 5A PER CONTACT 10mΩ MAX. |
| INSULATOR RESISTANCE: DIELECTRIC | 5000MΩ min. |
| WITHSTANDING VOLTAGE: | 1000V AC rms |

| $\mathbf{\nabla}$ |
|-------------------|

| | | | SW REFERENCE NO.: 630 COMBO ASSEMBLY | | | |
|--|--|--|--------------------------------------|------------------|-------|--|
| | | | DRAWN: C.B | DATE: JAN. 01/20 | 19 | |
| | | | CHECKED: | DATE: | | |
| | EDAG INC TORONTO, ONTARIO CANADA YOUR CONNECTION TO QUALITY & SERVICE | THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION. | SCALE: (IN C.A.D. 1:1) | SHEET 1 OF | 2 | |
| | | | DRAWING NUMBER: 630-2W2-650-3NA | | ISSUE | |
| | | | PART NUMBER: 630-2W2 | -650-3NA | 1 | |



HS

COMPLIANT

Г

