	л Солония и	m		0	Ξ	A		7
CHARACTERISTICS Standard : Based on MIL DTL 38999 Series III Shell Material ::::::::::::::::::::::::::::::::::::	22.6 Max	S			EXAMPLE			4
Shell Material 2. Auminum Source 2. Source Source 3. Source Source 3. Source Source 3. Source Source 3. Source Source Source Source Source Source Source Source Source Soure Source <tr< td=""><td>CHARACTERISTICS</td><td>Connector dimension Dim Nominal</td><td></td><td></td><td></td><td></td><td></td><td></td></tr<>	CHARACTERISTICS	Connector dimension Dim Nominal						
-Salt Spray : 500 hours -Mass : 17.66 g ± 10% Basic Series: 80 Basic Series: 80 SHELL TYPE : San ut Receptacle CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 11 ORIENTATION : N PLATING : Z Basic Series 01-10-2016 First Release MOD N° ORIENTATION : N SOURIAU WWW.SOURIAU.COM Insidocument is the property of souriation or communicated without permission PLATING : Z Black Zinc Nickel	 Shell Plating : Black Zinc Nickel -Insulator : Thermoplastic -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8µm minimum -Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories 	B 19.07+0.1/-0.15 R 32.5Max S 31.8±0.4 W 2.2+0.9/-0.1		due to a use of the Products wh the Specifications issued by either o (professional recommendat Countr FR	hich does not comply v f the Parties or by a th tion, technical notice.) ry Jurisdiction Not	vith ird party & Control List		2
BASIC SERIES: 8D 7 11 Z 22 P N BASIC SERIES: 8D 7 11 Z 22 P N SHELL TYPE : Standard Crimp Contact ORIENTATION : N General linear Tolerances: ± NPRDS / PROJECT 859 1 SHELL SIZE : 11 CONTACT TYPE : Standard Crimp Contact ORIENTATION : N SOURIAU WWW.SOURIAU.COM This document is the property of souriau it must not be reporty of communicated without permission SOURIAU WWW.SOURIAU.COM This document is the property of communicated without permission SOURIAU SOURIAU DRG N° SHEET	-Salt Spray : 500 hours							
BASIC SERIES. SU 7 - 11 2 2 22 P N P N NA Tolerances: Tolerances: 859 1 SHELL TYPE : Jam nut Receptacle ORIENTATION : N NA SOURIAU This document is the property of SOURIAU.COM SOURIAU SOURIAU 1 PLATING : Z = Black Zinc Nickel CONTACT LAYOUT : 11-22 FORMAT FORMAT SOURIAU DRG N° SHEET			Designed By:	Date:		TOMER DRAWING		
SUCRACILATION II-22 SUCRACI LATION II-22 SUCRACI LATION II-22	→ SHELL TYPE : Jam nut Receptacle CONTACT TYPE : Standard Crimp Contact	ORIENTATION : N	NA -{	Tolerances:	COM	859 This document is the proper SOURIAU it must not be reproduced	lor	1
A3 8D711Z22PN-C 1/2 H G F E D C B A			A3	8D711Z	22PN-C	A		

ſ	I	۵	П	m		C	σ	A	
4		Contact Layout 22*			J.	Panel cutout	M co		4
ω	Ctc A B C D	11-22 X Y 1.905 1.905 1.905 -1.905 -1.905 -1.905 -1.905 1.905				Dim Nominal B 19.59+0/-0.3 ØC 20.96+0.25/			3
N						due to a use of the Proo the Specifications issued by (professional recom		with lird party	2
					A 01-10-2016 ISS DATE Designed By:	First Release Latest modification - by Date:		MOI STOMER DRAWING	D N°
_					SCALE NA SOURIAU	Genera Tolera ±-	inces:	IPRDS / PROJECT 859 This document is the property of SOURIAU	1
	Н	G	F	E	FORMAT A3 D	SOUI		it must not be reproduced or communicated without permission SHE 2/	ET