


GL-2060M

Aliases (UNFGL2060MXXXX)

KEMET, GL, EMI/RFI Filters, Noise Suppression, 250 VAC



Click here for the 3D model.

Dimensions		
L	82mm NOM	
W	56mm NOM	
Н	38mm NOM	
Lead	Screw Terminals	

Packaging Specifications	
Packaging	Tray, Box
Packaging Quantity	8
Component Weight	205 g

General Information		
GL		
Metal Box		
Noise Filters		
With Exemptions		
UL, CSA, TUV		
30 K Self-Temperature Rise Max.		
Screw Terminals		
Screw		

Specifications	
Voltage AC	250 VAC
Voltage	1500 VAC Withstanding Voltage 1 Min. Line to Ground
Rated Current	6 A (AC/DC)
Rated Temperature	55°C
Temperature Range	-25/+55°C
Leakage Current	0.5 mA MAX (250 V 60 Hz)
Resistance	300 MOhms MIN Insulation 500 VDC 1 Min. Line To Ground

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.