

P-tec Corp. Tel:(866) 695 4162
 2405 Commerce Circle Tel:(719) 589 3122
 Alamosa CO 81101 Fax:(719) 589 3592
 www.p-tec.net



PL03 Series 3mm (T1) LED

Features

- *Popular 3mm Lens Style with Flange
- *1 GaP Green Chip used
- *Color Diffused Lens with a Wide Viewing Angle
- *High Intensity
- *Low Current Requirement
- *Reliable and Rugged
- *RoHS Compliant

Absolute Maximum Ratings at $T_A = 25^\circ\text{C}$

Power Dissipation.....	78mW
Reverse Voltage (<100 μ A).....	5.0V
Max Forward Current.....	30mA
Peak Forward Current (1/10 Duty Cycle, 0.1ms Pulse Width).....	100mA
Operating Temperature Range.....	-25 $^\circ\text{C}$ to +85 $^\circ\text{C}$
Storage Temperature Range.....	-40 $^\circ\text{C}$ to +100 $^\circ\text{C}$
Soldering Temperature (1.6mm below body).....	260 $^\circ\text{C}$ for 5 seconds

Electrical & Optical Characteristics at $T_A = 25^\circ\text{C}$

Part Number	Emitting Color	Chip Material	Peak Wave Length	Dominant Wave Length	Viewing Angle 2 θ $\frac{1}{2}$	Forward Voltage @20mA (V)		Luminous Intensity @20mA (mcd)	
						Typ	Max	Min	Typ
Color Diffused Lens			nm	nm	Deg				
PL03-CDG13	Green	GaP	567	572	56 $^\circ$	2.1	2.6	10.0	30.0

All dimensions are in **Millimeters**. Tolerance is $\pm 0.25\text{mm}$ unless otherwise specified. An epoxy meniscus may extend about 1 mm down the leads.

