ATGBICS

ATGBICS SFP-GE-T-ASR Cisco ASR1000-9000 Compatible Transceiver SFP 1000Base-T (Copper RJ45, Ext Temp, 100m)

Brand : ATGBICS

Product name : SFP-GE-T-ASR Cisco ASR1000-9000 Compatible Transceiver SFP 1000Base-T (Copper RJ45, Ext Temp, 100m)

Product code: SFP-GE-T-ASR-C

SFP-GE-T-ASR Cisco ASR1000-9000 Compatible Transceiver SFP 1000Base-T (Copper RJ45, Ext Temp, 100m)

ATGBICS SFP-GE-T-ASR Cisco ASR1000-9000 Compatible Transceiver SFP 1000Base-T (Copper RJ45, Ext Temp, 100m):

ATGBICS SFP-GE-T-ASR SFP operates on standard Category 5 unshielded twisted-pair copper cabling of link lengths up to 100m. Note this 1000BASE-T SFP module does NOT support 10/100/1000 auto negotiation and auto MDI/MDIX. It is fixed at 1000Base-T. Our product meets the specification of Cisco SFP-GE-T-ASR= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards. Note this SFP is built specifically for the Cisco ASR Range.

Performance

SFP transceiver type *	Copper
Maximum data transfer rate *	1250 Mbit/s
Interface type *	SFP
Single-mode fiber (SMF) supported	✖
Multi-mode fiber (MMF) supported	✖
SFP transceiver standard	TX
Maximum transfer distance	100 m
Ethernet LAN	✔
Ethernet interface type	Gigabit Ethernet
Copper ethernet cabling technology	1000BASE-TX
Auto MDI/MDI-X	✖
Digital Diagnostics Monitoring (DDM)	✖

Features

Product colour	Silver
Housing material	Metal
Plug and Play	✔
Hot-Plug support	✔
Hot-swap	✔
Easy to install	✔
Country of origin	United Kingdom
Brand compatibility	Cisco
Certification	CE, FCC, RoHS

Power

Input voltage	3.3 V
Maximum voltage	4 V
Power consumption (typical)	1.3 W

Operational conditions

Minimum operating temperature	-5 °C
Maximum operating temperature	85 °C
Operating temperature (T-T)	-5 - 85 °C
Storage temperature (T-T)	-40 - 85 °C
Operating relative humidity (H-H)	5 - 85%
Storage relative humidity (H-H)	5 - 85%

Weight & dimensions

Width	13.4 mm
Depth	56.6 mm
Height	8.5 mm
Weight	24 g

Packaging data

Number of products included	1 pc(s)
Package type	Box

Technical details

Sustainability compliance	✔
Sustainability certificates	RoHS
Doesn't contain	Lead

5056468701367