

6

5

4

3

2

1

PART NUMBER	ENGINEERING NO.	LENGTH ± TOLERANCE
1300500262	ENQ3135M010	3' 3" +2.19"/-0" [1M +55.6/-0 mm]

NOTES:

1) MATERIAL: SEE TABLE
 2) FINISHES: SEE TABLE
 3) CABLE: #24/8 SHIELDED TWISTED PAIR, PVC
 4) ELECTRICAL DATA:
 ACCORDING TO CAT5e ETHERNET STANDARD
 MAX. VOLTAGE: 30V
 MAX. CURRENT 1.5A
 5) ENVIRONMENTAL:
 PROTECTION IP67
 TEMPERATURE RANGE: -20°C TO +80°C
 6) WRAP LABEL IS MARKED WITH P/N & DATE CODE.
 7) ASSEMBLY IS RoHS COMPLIANT.

WIRE LIST	
PIN #	COLOR
1	WHITE/ORANGE
2	ORANGE
3	WHITE/GREEN
4	BLUE
5	WHITE/BLUE
6	GREEN
7	WHITE/BROWN
8	BROWN
GND	DRAIN WIRE

ITEM	QTY.	DESCRIPTION	MATERIAL	FINISH
6	1	RJ45 PLUG	POLYCARBONATE	CLEAR
5	1	COUPLING NUT	ABS	BLACK
4	1	LABEL	PLASTIC FILM	BLACK/YELLOW
3	1	RJ45 PLUG	POLYCARBONATE	CLEAR
2	1	BOOT	PVC	BLACK
1	1	ETHERNET CABLE-CAT5E	PVC JACKET	BLACK

RELEASE DRAWING EC NO: WNA2010-0442 DRWN: TVICKERS 2010/01/18 CHKD: B.WOODMA APPR: DTTITUS 2010/01/19	QUALITY SYMBOLS
	$\nabla = 0$ $\nabla C = 0$
	DESCRIPTION
	REV

GENERAL TOLERANCES (UNLESS SPECIFIED)		
	mm	INCH
4 PLACES	±---	±---
3 PLACES	±---	±.005
2 PLACES	±0.13	±.010
1 PLACE	±0.25	±.020
ANGULAR ±1/2°		
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		

DIMENSION STYLE		SCALE	DESIGN UNITS	THIRD ANGLE PROJECTION
IN		1:1	INCH	
DRAWN BY	DATE	TITLE		
---	---	ETHERNET MMJ IND./RJ45 568-B SHIELD ASSEMBLY PVC STRANDED CABLE		
CHECKED BY	DATE	MOLEX INCORPORATED		
B.WOODMA	2010/01/18	DOCUMENT NO. SD-130050-024		
APPROVED BY	DATE	SHEET NO. 1 OF 1		
DTITUS	2010/01/19			
MATERIAL NO.	SEE CHART			
SIZE	A	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		

6

5

4

3

2

1