

## Specification Sheet

Part Number: 184-21006

Narrow fingers reduce fanning of the wires to the terminal blocks, presenting a neater appearance.

Each finger is provided with a double restriction to hold wires in the bottom portion of the duct, allowing for easier installation.

Mounting holes are uniform in size and are offered every 2 inches to accommodate compact designs and ease installation.

Optional covers snap on and off easily, and are provided with a non-slip lining that insures the covers remain in place during vibration.



High-Density Slotted-Wall Wiring Duct, 2" x 1", Non-Adhesive, PVC, Black, 30ft/box

**Article Number** 184-21006

**Type** SLHD2X1

**Color** Black (BK)

**Quantity Per** box

**Product Description** HellermannTyton High-Density Slotted Wall Wiring Duct features narrow fingers equaling a 2-to-1 finger ratio compared to standard slotted wiring duct. With the narrow fingers, compact designs and components are more easily accommodated.

**Short Description** High-Density Slotted-Wall Wiring Duct, 2" x 1", Non-Adhesive, PVC, Black, 30ft/box

**Global Part Name** SLHD2X1-PVC-BK

**Length L (Imperial)** 6.0

**Length L (Metric)** 1.83

**Width W (Imperial)** 2.0

**Width W (Metric)** 50.8

**Height H (Imperial)** 1.06

**Height H (Metric)** 26.9

**Mounting Hole Centers (Imperial)** 2.0

**Material** Polyvinylchloride (PVC)

**Material Shortcut** PVC

**Flammability** Self-extinguishing

**Halogen Free** No

**Operating Temperature** +122°F (+50°C)

**Reach Compliant (Article 33)** No

<b>ROHS Compliant</b>	Yes
<b>Certification/Specification</b>	EN 50085-1:2005 + A1:2013 EN 50085-2-3_1A CSA UL
<b>UL Recognized (US)</b>	Yes
<b>Package Quantity (Imperial)</b>	30
<b>Package Quantity (Metric)</b>	9.14
<b>Customs Number</b>	3925900000

© 2021 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)