[т		۵	-	п		п		D		O
4 3			W Thread			S	ØA				
				К	eying Showr	n as example					
	CHARACTERISTICS				, 0			-			
	-Standard : Based on MIL-	DTL-38999 Series	111			Dim	r dimension Nominal				
2	-Shell Plating : 1 -Insulator : 7 -Contacts : 0 -Seals & Grommet : 9 -Contact Plating : 0	Stainless Steel Passivated Thermoplastic Copper Alloy Silicon Elastomer Gold over copper A	Alloy 0.8µm minim	um		A B R S W VV THREAD	38.1±0.3 23.82+0.1/-0.15 32.5Max 34.9±0.4 2.2+0.9/-0.1 M18x1-6g				SOURIAU shal due to a us the Specification (profes
	-Delivered with Souriau co	ontacts and Access	sories								
		-65°C to +200°C 500 hours							А	28-09-2016	First Release
	Surespiny								ISS	DATE	Latest modifica
									Designe	d By:	Date
									•	TITLE	
	BASIC SERIES:	8D	7 - 13	К 04	S E				SCA	E	$\neg \phi$
	SHELL TYPE : Jam nut Rec	ceptacle							NA	<u> </u>	$\neg \Psi$
	CONTACT TYPE : Standa	rd Crimp Contact					ORIE	NTATION : E	SO	URIAU	WWV
	SHELL SIZE : 13					CONTAG	CT TYPE : SOCKET(5	00 Matings)			~~~~
	PLATING : K = Pas	sivated	-				CONTACT LAY	OUT : 13-04	FORM		
			T					1	A	3	
	Н		G	F	-		E	·/	D		С

 $\mathbf{\mathbf{n}}$

	σ	A				
				4		
LAYOUT SHOWN AS EXAMPLE						
all not be liable for any non-conformity or damage use of the Products which does not comply with ons issued by either of the Parties or by a third party essional recommendation, technical notice.) Country Jurisdiction & Control List FR 2 PN: 8D713K04SE						
ation - by te: Stainless Steel		customer drawing le 8D series	MOD N°			
General linear Tolerances: ± W.SOURIAU.COI	M	NPRDS / PROJECT 859 This document is the property of SOURIAU it must not be reproduced or communicated without permission				
SOURIAU D 8D713K04		A	SHEET 1/2			

Г	D I	г	т	
4	Contact Layout \xrightarrow{P}^{+Y} \xrightarrow{P}^{+Y} \xrightarrow{P}^{+Y} \xrightarrow{P}^{+}			Panel cutout JAM NUT RECEPTACLE (TYPE 7)
	Contact position ID X-axis (mm) Y-axis (mm) A +.000 (0.00) +.150 (3.81) B +.146 (3.71) +.035 (0.89) C +.000 (0.00) 083 (2.11) D 146 (3.71) +.035 (0.89) Shell Arrangement no. Number of contacts Size contacts Service rating Contact location 13 -4 4 16 I All	Supersedes MS20051-4		
ω				Dim Nominal B 24.26+0/-0.25 ØC 25.65+0.25/-0
				SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)
2				Country Jurisdiction & Control List 2 FR Not Listed 2 PN: 8D713K04SE
				A 28-09-2016 First Release MOD N° ISS DATE Latest modification - by MOD N° Designed By: Date: CUSTOMER DRAWING
				TITLE Stainless Steel Receptacle 8D series
_				SCALE General linear NPRDS / PROJECT NA Image: scale s
				SOURIAU WWW.SOURIAU.COM This document is the property of SOURIAU it must not be reproduced or communicated without permission
			1	FORMATSOURIAU DRG N°SHEETA38D713K04SE-C2/2
L	H G	F	E	