


**C1206A103J1XAC** GR900 SMD Space, Ceramic, 0.01 uF, 5%, 100 VDC, BX, N/A, 1206



Click here for the 3D model.

Dimensions		
Chip Size	1206	
L	3.07mm +/-0.38mm (0.121 in +/-0.015 in)	
W	1.52mm +/-0.38mm (0.06 in +/-0.015 in)	
Т	1.6mm MAX (0.063 in MAX)	
В	0.51mm +/-0.25mm (0.02 in +/-0.01 in)	

**Packaging Specifications** 

Packaging

Bulk, Bag

General Information			
Series	GR900 SMD Space		
Style	SMD Chip		
RoHS	Yes		
Termination	Tin		
Failure Rate	N/A		
Testing and Reliability	GR900 CSAM A		
AEC-Q200	No		
Shelf Life	78 Weeks		
MSL	1		

Specifications			
Capacitance	0.01 uF		
Capacitance Tolerance	5%		
Voltage DC	100 VDC		
Temperature Range	-55/+125°C		
Temperature Coefficient	BX		

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.