FG   1   BR   6 - A

COLOR
BR=BROWN

ADHESIVE
BACKED

LARGE OPENING
CROSSECTIONAL
AREA (.1 in²)

LENGTH
6:6 FOOT
50:50 FOOT

FLOORGUARD

NOTES: COLOR CODE: BR=BROWN, YL=SAFETY YELLOW,
EI=ELECTRICAL IVORY, BL=BLACK
LENGTH: 6 FOOT $^{+6}_{-.2}$ in. (1.83m $^{+152mm}_{-5mm}$)
50 FOOT $^{+6}_{-.2}$ in. (15.24m $^{+152mm}_{-5mm}$)
WEIGHT: .08 lb/ft, (.115 Kg/m)

ADHESIVE BACKING
TWO SIDED CLOTH TAPE .014(.4)
THICK WITH PROTECTIVE LINER.
(TAPE TO BE APPLIED AT TIME OF
APPLICATION).

.25
[6.4]

.17
[4.3]

.13
[3.3]
(TYP)

1.00
[25.4]

1.25
[31.8]

.27
[6.9]

INSTRUCTIONS
1. CUT FLOORGUARD TO DESIRED LENGTH.
2. INSERT WIRES INTO FLOORGUARD.
3. APPLY TAPE TO FLOORGUARD. (TAPE IS TO BE CENTRALLY
   LOCATED ON THE FLOORGUARD AS SHOWN ON THE DRAWING.)
4. REMOVE RELEASE LINER FROM TAPE AND PLACE FLOORGUARD
   ON A CLEAN, DRY SURFACE.
5. APPLY PRESSURE TO ENTIRE LENGTH OF FLOORGUARD TO
   OBTAIN MAXIMUM ADHESION.

WPXD.MISC.DUCT.CUST-2
DWG NAME   LAYER NO.
FG1   20

CUSTOMER DRAWING

CAD FILENAME/LAYERS
DIMENSIONS IN PARENTHESIS ARE IN METRIC

PANDUIT CORP. TINLEY PARK, ILLINOIS

FLOORGUARD FG1

UNLESS OTHERWISE SPECIFIED,
DIMENSIONAL TOLERANCES ARE:
(.X) :   (.XXX) :
(.XX) :.05(1.3) ANGLES :

UNLESS OTHERWISE SPECIFIED,
ALL DIMENSIONS ARE GIVEN
IN INCHES, THIRD ANGLE PROJECTION.

DRAWN BY
DW

MAT'L:
FLEXIBLE
VINYL

SCALE
NONE

DATE
12-4-90

DRAWING NO.
34153-2

DWG
A
SIZE

CHK'D
CEF

REV	DATE	BY	CHK	DESCRIPTION	ECN - R		CUST	SUP
R	12-5-90	DW	CEF	RELEASED TO PRODUCTION	34153-2	R WJB		