т <u>О</u> т т			
Z			
Keying Shown as example	LAYOUT SHOWN AS EXAMPLE		
CHARACTERISTICS Connector dimension			
-Standard : Based on MIL-DTL-38999 Series III ØS 35.7 Max			
-Shell Material     : Aluminium       -Shell Plating     : Olive drab Cadmium       -Shell Plating     : Olive drab Cadmium       -Insulator     : Thermoplastic       -Contacts     : Copper Alloy	SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)		
-Seals & Grommet : Silicon Elastomer	Country Jurisdiction & Control List		
-Contact Plating : Gold over copper Alloy 0.8μm minimum -Durability : 500 Mating cycles	FR   Not Listed		
-Delivered with Souriau contacts and Accessories	PN: 8D517W22SE		
-Temperature Range -65°C to +175°C	A 17-10-2016 First Release		
-Salt Spray : 500 hours	ISS DATE Latest modification - by MOD	N°	
	Designed By: Date: CUSTOMER DRAWING		
	TITLE Aluminium Plug 8D series		
BASIC SERIES: 8D 5 - 17 W 22 S E	SCALE General linear NPRDS / PROJECT		
SHELL TYPE : Plug with RFI Shielding	NA Tolerances: 859		
CONTACT TYPE : Standard Crimp Contact ORIENTATION	This document is the property of		
SHELL SIZE : 17 CONTACT TYPE : SOCKET(500 Matin	- SOURIAU WWW.SOURIAU.COIVI it must not be reproduced or		
PLATING : W = Olive drab Cadmium CONTACT LAYOUT : 17-		ET	
	A3 8D517W22SE-C 1/2		

	Ŧ	۵	п –	m		0
4		Contact Layout 22				
	Ctc A B C	2#12 2#8 Triax 17-22 X Y 0 4.57 6.32 0 0 -4.57				
3		-6.32 0				SOURIAU shall not be liable for ar due to a use of the Products w
2						the Specifications issued by either of (professional recommenda
					A 17-10-20 ISS DATE Designed By: TITLE SCALE	16 First Release Latest modification - by Date: Alumin General linear
1					SOURIA SOURIA	Tolerances:
	Н	G	F	E	D	C

