	I G T	m		0	B	_
4	R 22.6 Max (t) (t) (t) (t) (t) (t) (t) (t) (t) (t)	S				4
	Keying Sho CHARACTERISTICS -Standard : Based on MIL-DTL-38999 Series III	own as example Connector dimension Dim Nominal				
2	-Shell Material: Aluminium-Shell Plating: Olive drab Cadmium-Insulator: Thermoplastic-Contacts: Copper Alloy-Seals & Grommet: Silicon Elastomer-Contact Plating: Gold over copper Alloy 0.8μm minimum-Durability: 500 Mating cycles	A 38.1±0.3 B 23.82+0.1/-0.15 R 32.5Max S 34.9±0.4 W 2.2+0.9/-0.1 VV THREAD M18x1-6g		SOURIAU shall not be liable for any no due to a use of the Products which the Specifications issued by either of the (professional recommendation, Country FR	does not comply with e Parties or by a third party technical notice.) Jurisdiction & Control List Not Listed	2
	 -Delivered with Souriau contacts and Accessories -Temperature Range : -65°C to +175°C -Salt Spray : 500 hours -Mass : 24.32 g ± 10% 		A 29-09-2016	PN: 8D713W3 First Release Latest modification - by	S5PD MOD N°	
			Designed By:	Date: Aluminium R	customer drawing eceptacle 8D series	
_	BASIC SERIES: 8D 7 - 13 W 35 P D SHELL TYPE : Jam nut Receptacle)	SCALE -{	General linear Tolerances: ±	NPRDS / PROJECT 859	1
	CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 13	ORIENTATION : D CONTACT TYPE : PIN(500 Matings)	SOURIAU	WWW.SOURIAU.CO	communicated without permission	
	PLATING : W = Olive drab Cadmium	CONTACT LAYOUT : 13-35	format A3	SOURIAU D 8D713W35		
	H G F	E	D	C	BA	

Г	T	Q	т	Ш	t	2	0	ω		۵	,
4	Con -x	act Layout					Panel cutout	Ā			4
	Contact Location position X-axis Y-axis ID (mm) (mm) 1 +.045 (1.14) +.197 (5.12) 2 +.126 (3.20) +.158 (4.13) 3 +.182 (4.62) +.088 (2.14) 4 +.203 (5.16) +.000 (0.15) 5 +.126 (3.20) 158 (4.12) 6 +.126 (3.20) 158 (4.12) 7 +.045 (1.14) 197 (5.16)	ID (mm) (mm) 00) 12 182 (4.62) +.088 (2.24) 13 126 (3.20) +.158 (4.01) 24) 14 045 (1.14) +.197 (5.00) 00) 15 +.045 (1.14) +.107 (2.72) 24) 16 +.117 (2.97) +.026 (0.66) 01) 17 +.093 (2.36) 075 (1.91)					ØC				
ى ع	8 045 (1.14) 197 (5. 9 126 (3.20) 158 (4. 10 182 (4.62) 088 (2. 11 203 (5.16) +.000 (0.	00) 19 093 (2.36) 075 (1.91) 01) 20 117 (2.97) +.026 (0.66) 24) 21 045 (1.14) +.107 (2.72)					Dim Nominal B 24.26+0/-0 ØC 25.65+0.25	.25			3
							the Specifications issued by	ducts which does not cor	nply with y a third party		
2								Country Jurisdi FR	ction & Control List Not Listed		2
					-	A 29-09-2016 ISS DATE	PN: 8D	713W35PD		MOD N°	-
					-	Designed By:	Date:		CUSTOMER DRAWING		-
					_	TITLE		ninium Receptacl			
_						SCALE - NA		al linear ances: 	NPRDS / PROJECT 859		1
						SOURIAU	WWW.SOUR	IAU.COM	This document is the SOURIAU it must not be repro communicated withou	oduced or	
						format A3		RIAU DRG N° '13W35PD-C		SHEET 2/2	
L	Н	G	F	Е			С	В		A	J