


SSR21NVS-M12220

Aliases (UALS21V1222000)

KEMET, SSR21NVS-M/NHS-M, AC Line Filters, Common Mode, 22 mH



Click	here	for	the	3D	mode	ı

Dimensions	
L	22mm MAX
Т	16mm MAX
Н	27mm MAX
LL	3.5mm +/-0.5mm
S	13mm +/-0.5mm
S1	10mm +/-0.5mm
Wire Size	0.35mm

Packaging Specifications	
Packaging	Tray
Packaging Quantity	450
Component Weight	14.5 g

General Information			
Series	SSR21NVS-M/NHS-M		
Style	Through-Hole		
Features	High Performance, High Impedance, Strong Inductance		
RoHS	Yes		
Miscellaneous	60 (K) Temperature Rise Max.		
Core	Mn-Zn Ferrite		

Specifications	
Voltage AC	250 VAC
Inductance	22 mH (10 kHz)
Current	1.2 A
Temperature Range	-25/+120°C
DC Resistance	350 mOhms

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.