

## Crimping pliers - CRIMPFOX-TC MP - 1212510

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Crimping pliers, for turned contacts, universal cross section setting, up to a maximum of 2.5 mm<sup>2</sup>, digital display with 0.01 mm increments, pressure lock can be unlocked, including positioning tool

### Your advantages

- Universal adjustment for precise processing of corresponding cross sections
- Crimping pliers for processing turned contacts of up to 2.5 mm<sup>2</sup>
- The integrated positioning tool ensures that the contacts are perfectly aligned



### Key Commercial Data

Packing unit	1 pc
GTIN	 4 046356 555500
GTIN	4046356555500

### Technical data

#### Dimensions

Length (b)	175 mm
------------	--------

#### General

Color	black
Compression	Four-mandrel crimping
Type of contact	Turned contacts
Weight	850 g
Min. cross section	0.08 mm <sup>2</sup>
Max. cross section	2.5 mm <sup>2</sup>
AWG min	28
AWG max	14

### Environmental Product Compliance

# Crimping pliers - CRIMPFOX-TC MP - 1212510


## Technical data

### Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"
California Proposition 65	Further information on California's prop. 65 is available under "Downloads" in the manufacturer's declaration

## Drawings

Pictogram



## Approvals

Approvals

## Crimping pliers - CRIMPFOX-TC MP - 1212510

### Approvals

Approvals


EAC

---

Ex Approvals

---

### Approval details

EAC		RU x- DE.xx08.B.02974
-----	---	--------------------------

---

Phoenix Contact 2019 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>