



- .035 DIA HOLE IS RECOMMENDED FOR .125 MAX THICK P.C. BOARD
- CONNECTOR MATES WITH ANY AMP 26 POSN PLUG
- POST TIPS WILL FALL WITHIN Ø.020 TRUE POSITION OF EACH OTHER.

- 5 FINISH: CADMIUM PER QQ-P-416
- 6 FINISH: ZINC PLATED PER ASTM-B-633, .000200-.000400 THK WITH SUPPLEMENTARY CHROMATE (Cr3+)

PLATED PER 6	5-211575-1
PLATED PER 5	211575-1
DESCRIPTION	PART NO.

THIS DRAWING IS A CONTROLLED DOCUMENT.		DIN 8-11-97		C.C.THOMAS													
DIMENSIONS: INCHES		TOLERANCES UNLESS OTHERWISE SPECIFIED:		CIRK 11-24-97													
<table border="1"> <tr><td>0 PLC</td><td>± .005</td></tr> <tr><td>1 PLC</td><td>± .005</td></tr> <tr><td>2 PLC</td><td>± .005</td></tr> <tr><td>3 PLC</td><td>± .005</td></tr> <tr><td>4 PLC</td><td>± .005</td></tr> <tr><td>ANGLES</td><td>± .005</td></tr> </table>		0 PLC	± .005	1 PLC	± .005	2 PLC	± .005	3 PLC	± .005	4 PLC	± .005	ANGLES	± .005	APVD 11-24-97		NAME	
0 PLC	± .005																
1 PLC	± .005																
2 PLC	± .005																
3 PLC	± .005																
4 PLC	± .005																
ANGLES	± .005																
MATERIAL SEE CALLOUTS		FINISH SEE CALLOUTS		H.WYNKOOP													
CUSTOMER DRAWING		SCALE 4:1		SHEET 1 OF 1													
REV J		DRAWING NO. A100779		C=211575													