т Q Т т		
		4
	LAYOUT SHOWN AS EXAMPLE	3
	LATOUT SHOWIN AS EXAMPLE	
Keying Shown as example		
CHARACTERISTICS Connector dimension -Standard : Based on MIL-DTL-38999 Series III Dim Nominal		
Shell Material Aluminium		\vdash
-Shell Plating : Nickel VV THREAD M31x1-6g	SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with	
-Insulator : Thermoplastic	the Specifications issued by either of the Parties or by a third party	
-Contacts : Copper Alloy	(professional recommendation, technical notice.)	
-Seals & Grommet : Silicon Elastomer	Country Jurisdiction & Control List	
► -Contact Plating : Gold over copper Alloy 0.8µm minimum	FR Not Listed	2
-Durability : 500 Mating cycles		
-Delivered with Souriau contacts and Accessories	PN: 8D521F39BN	
-Temperature Range65°C to +200°C	A 06-10-2016 First Release	_
-Salt Spray : 48 hours		
	ISS DATE Latest modification - by MOD N Designed By: Date: CUSTOMER DRAWING	<u> </u>
	TITLE Aluminium Plug 8D series	
BASIC SERIES: 8D 5 - 21 F 39 B N SHELL TYPE : Plug with RFI Shielding	SCALE General linear NPRDS / PROJECT NA ± 859	1
CONTACT TYPE : Standard Crimp Contact ORIENTATION	This document is the property of	- '
SHELL SIZE : 21 CONTACT TYPE : SOCKET(500 Matin		
PLATING : F = Nickel CONTACT LAYOUT : 21		
	0000011000110	
H I G I F I E	D C B A	

