

Ultra-Low Capacitance ESD Protection Diodes

Micro-Packaged Diodes for ESD Protection

ESDL3552B

The ESDL3552B is designed to protect voltage sensitive components that require ultra-low capacitance from ESD and transient voltage events. Excellent clamping capability, low capacitance, high breakdown voltage, high linearity, low leakage, and fast response time make these parts ideal for ESD protection on designs where board space is at a premium. It has industry leading capacitance linearity over voltage making it ideal for high-speed data line protection applications.

Features

- Industry Leading Capacitance Linearity Over Voltage
- Ultra-Low Capacitance: 0.25 pF
- Insertion Loss: 0.26 dB @ 5 GHz
- 0201 Isolated DSN Package: 0.62 mm x 0.32 mm
- Stand-off Voltage: 5.0 V
- Low Leakage: < 50 nA
- Low Dynamic Resistance: < 1.0 Ω
- These Devices are Pb-Free, Halogen-Free/BFR-Free and are RoHS Compliant

Typical Applications

- High Speed Data Line Protection
- USB 2.0, USB 3.0, USB 3.1

MAXIMUM RATINGS (T_A = 25°C unless otherwise noted)

Rating	Symbol	Value	Unit
IEC 61000-4-2 Level 4 (Contact) (Note 1) IEC 61000-4-2 Level 4 (Air) (Note 1)	ESD	±20 ±20	kV
Maximum Peak Pulse Current IEC 61000-4-5 8/20 μs (Lightning) (Note 2)	I _{PP}	2.0	A
Total Power Dissipation (Note 3) @ T _A = 25°C Thermal Resistance, Junction-to-Ambient	P _D R _{θJA}	300 400	mW °C/W
Junction and Storage Temperature Range	T _J , T _{stg}	-55 to +150	°C
Lead Solder Temperature - Maximum (10 Second Duration)	T _L	260	°C


Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. Non-repetitive current pulse at T_A = 25°C, per IEC61000-4-2 waveform.
2. Non-repetitive current pulse at T_A = 25°C, per IEC61000-4-5 waveform.
3. Mounted with recommended minimum pad size, DC board FR-4




X4DFN3
CASE 718AB

MARKING DIAGRAM



A = Specific Device Code



ORDERING INFORMATION

Device	Package	Shipping†
ESDL3552BPFCT5G	X4DFN3 (Pb-Free/ Halide Free)	10000 / Tape & Reel

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, [BRD8011/D](#).


ESDL3552B

ELECTRICAL CHARACTERISTICS

($T_A = 25^\circ\text{C}$ unless otherwise noted)

Symbol	Parameter
I_{PP}	Maximum Reverse Peak Pulse Current
V_C	Clamping Voltage @ I_{PP}
V_{RWM}	Working Peak Reverse Voltage
I_R	Maximum Reverse Leakage Current @ V_{RWM}
V_{BR}	Breakdown Voltage @ I_T
I_T	Test Current

*See Application Note [AND8308/D](#) for detailed explanations of datasheet parameters.



ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ unless otherwise noted)

Parameter	Symbol	Condition	Min	Typ	Max	Unit
Reverse Working Voltage	V_{RWM}	Between any two pins (-40°C to $+85^\circ\text{C}$)			5.0	V
Breakdown Voltage	V_{BR}	$I_T = 10\text{ mA}$, Between any two pins (-40°C to $+85^\circ\text{C}$)	6.5	10.2	11.5	V
		$I_T = 1\text{ mA}$, Between any two pins	7.0	9.3	11	
Reverse Leakage Current	I_R	$V_{RWM} = 5.0\text{ V}$, $T_A = 25^\circ\text{C}$		0.001	0.05	μA
		$V_{RWM} = 5.0\text{ V}$, $T_A = 85^\circ\text{C}$		0.001	0.25	μA
Clamping Voltage TLP	V_C	$I_{PP} = 4\text{ A}$ } IEC 61000-4-2 Level 1 equivalent ($\pm 2\text{ kV}$ Contact, $\pm 4\text{ kV}$ Air) Pin 1 to Pin 2, Pin 3 to Pin 2		14.5		V
		$I_{PP} = 16\text{ A}$ } IEC 61000-4-2 Level 4 equivalent ($\pm 8\text{ kV}$ Contact, $\pm 16\text{ kV}$ Air) Pin 1 to Pin 2, Pin 3 to Pin 2		21.5		V
Reverse Peak Pulse Current	I_{PP}	IEC61000-4-5 (8x20 μs), Between any two pins	2.0	3.0		A
Clamping Voltage (8x20 μs)	V_C	$I_{PP} = 2\text{ A}$		14	18	V
Dynamic Resistance	R_{DYN}	100 ns TLP, Pin 1 to Pin 2, Pin 3 to Pin 2		0.58		Ω
Junction Capacitance	C_J	$V_R = 0\text{ V}$, $f = 1\text{ MHz}$, Between any two pins		0.25	0.30	pF
Capacitance Linearity	C_Δ	$V_R = 0\text{ V}$ to 5 V , $f = 1\text{ MHz}$		0.03		pF
Insertion Loss	I_L	$f = 2.5\text{ GHz}$		0.16		dB
		$f = 5.0\text{ GHz}$		0.26		
		$f = 10.0\text{ GHz}$		0.41		

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.




Figure 1. ESD Clamping Voltage Screenshot Positive 8 kV Contact per IEC61000-4-2




Figure 2. ESD Clamping Voltage Screenshot Negative 8 kV Contact per IEC61000-4-2

TYPICAL CHARACTERISTICS




Figure 3. Positive TLP I-V Curve




Figure 4. Negative TLP I-V Curve




Figure 5. Positive Clamping Voltage vs. Peak Pulse Current ($t_p = 8/20 \mu s$)




Figure 6. Negative Clamping Voltage vs. Peak Pulse Current ($t_p = 8/20 \mu s$)




Figure 7. Breakdown Voltage




Figure 8. Line Capacitance, $f = 1 \text{ MHz}$

ESDL3552B

TYPICAL CHARACTERISTICS




Figure 9. Insertion Loss

MECHANICAL CASE OUTLINE

PACKAGE DIMENSIONS


ON Semiconductor®



SCALE 8:1

X4DFN3 0.62x0.32, 0.225P
CASE 718AB
ISSUE A


DATE 13 MAR 2018



- NOTES:
1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
 2. CONTROLLING DIMENSION: MILLIMETERS.


MILLIMETERS			
DIM	MIN	NOM	MAX
A	0.175	0.20	0.225
A1	0.000	0.015	0.030
b	0.23	0.25	0.27
D	0.595	0.620	0.645
E	0.295	0.320	0.345
e	0.225 BSC		
L	0.08	0.10	0.12

GENERIC MARKING DIAGRAMS*



X = Specific Device Code

RECOMMENDED MOUNTING FOOTPRINT*



DIMENSIONS: MILLIMETERS

See Application Note AND8398/D for more mounting details
 *For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

DOCUMENT NUMBER:	98AON64083G	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.
DESCRIPTION:	X4DFN3 0.62x0.32, 0.225P	PAGE 1 OF 1

ON Semiconductor and are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. ON Semiconductor does not convey any license under its patent rights nor the rights of others.

onsemi, **Onsemi**, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:

Email Requests to: orderlit@onsemi.com

onsemi Website: www.onsemi.com

TECHNICAL SUPPORT

North American Technical Support:

Voice Mail: 1 800-282-9855 Toll Free USA/Canada

Phone: 011 421 33 790 2910

Europe, Middle East and Africa Technical Support:

Phone: 00421 33 790 2910

For additional information, please contact your local Sales Representative