



.XX ±0.13

.XXX ±0.05










NOTES:

MATERIAL:
HOUSING:
SHELL:
CONTACT:THERMOPLASTIC POLYESTER, UL94V-0
STEEL, NICKEL PLATED
COPPER ALLOY, GOLD FLASH PLATEDOPERATING TEMPERATURE:-55°C ~ 125°CPOWER/CO-AX CONTACT RATING:
SIGNAL CONTACT CURRENT RATING:
SIGNAL CONTACT RESISTANCE:30A (CURRENT)
SA PER CONTACT
10mΩ MAX.


INSULATOR RESISTANCE: DIELECTRIC WITHSTANDING VOLTAGE:

1000V AC rms

5000MΩ min.



	COMBINATION D-SUB		SW REFERENCE NO.: 630 COMBO ASSEMBLY		
			DRAWN: C.B	DATE: JAN. 01/20	19
			CHECKED:	DATE:	
	EDAC INC	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND	SCALE: (IN C.A.D. 1:1)	SHEET 1 OF	2
YOUR CONNECTION TO	TORONTO, ONTARIO CANADA	SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	DRAWING NUMBER: 630-17W2250-3NE		ISSUE
	CONNECTION TO QUALITY & SERVICE		PART NUMBER: 630-17W	2250-3NE	1





THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

