ATGBICS GLC-TA Cisco Compatible Transceiver SFP 10/100/1000Base-T (RJ45, Copper, 100m)

Brand : ATGBICS

Product code: GLC-TA-C

Product name : GLC-TA Cisco Compatible Transceiver SFP 10/100/1000Base-T (RJ45, Copper, 100m)

GLC-TA Cisco Compatible Transceiver SFP 10/100/1000Base-T (RJ45, Copper, 100m)

ATGBICS GLC-TA Cisco Compatible Transceiver SFP 10/100/1000Base-T (RJ45, Copper, 100m):

ATGBICS GLC-TA SFP operates on standard Category 5 unshielded twisted-pair copper cabling of link lengths up to 100m. Cisco 1000BASE-T SFP modules support 10/100/1000 auto negotiation and auto MDI/MDIX. Our product meets the specification of Cisco GLC-TA= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards.

ATGBICS GLC-TA Cisco Compatible Transceiver SFP 10/100/1000Base-T (RJ45, Copper, 100m). SFP transceiver type: Copper, Maximum data transfer rate: 1250 Mbit/s, Interface type: SFP. Product colour: Silver, Housing material: Metal, Country of origin: China. Input voltage: 3.3 V, Maximum voltage: 4 V, Power consumption (typical): 1.3 W. Width: 13.4 mm, Depth: 56.6 mm, Height: 8.5 mm. Number of products included: 1 pc(s), Package type: Box





Performance		Features	
SFP transceiver type * Maximum data transfer rate *	SFP ★ TX 100 m ✓ Gigabit Ethernet 10BASE-T, 100BASE-TX, 1000BASE- TX ✓	Certification	CE, FCC, RoHS
		Power	
Interface type * Single-mode fiber (SMF) supported Multi-mode fiber (MMF) supported SFP transceiver standard Maximum transfer distance Ethernet LAN Ethernet interface type Copper ethernet cabling technology Auto MDI/MDI-X Digital Diagnostics Monitoring		Input voltage Maximum voltage Power consumption (typical) Operational conditions Maximum operating temperature Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	3.3 V 4 V 1.3 W 70 °C 0 - 70 °C -40 - 85 °C 5 - 85% 5 - 85%
(DDM)	^	Weight & dimensions Width	12.4 mm
Features Product colour Housing material Plug and Play	Silver al Metal rt I in China	Depth Height Weight	13.4 mm 56.6 mm 8.5 mm 24 g
Hot-Plug support		Packaging data	
Hot-swap Easy to install		Number of products included Package type	1 pc(s) Box
Country of origin Brand compatibility		Technical details	
		Sustainability compliance Sustainability certificates Doesn't contain	✔ RoHS Lead



5056468753915

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.