


CIRCUIT DIAGRAM

SPECIFICATION

1. Rating : DC 30V 0.5A;
2. Contact resistance: $\leq 0.03 \Omega$;
3. Insulation resistance: $\geq 100M \Omega$ (DC250V) ;
4. Withstand voltage: 500VAC ;
5. Insertion and extraction force: 3-20N;
6. Life test: 5,000 cycles.



16-040	05/20/16	B	REVISID PRODUCT DRAWING	VF	TH
06-019	01/13/06	A	REVISID CIRCUIT DIAGRAM	RH	JY
ECN#	DATE	SYM	REVISION RECORD	AUTH	BY

PROJECTION			SCALE		
			N/A		
TOLERANCE			DEC. MILLIMETERS		
EXCEPT AS NOTED			L:54±0.2		
			4L:516±0.3		
			L:16±0.4		
			ANG. N/A		
TITLE					
EARPHONE JACK 3.50mm DIA.-RHS COMPLIANT			DATE		SHEET
			DR. Jlh	12/01/05	1 OF 1
			CK. JY	PRE- DRAWING NO. 2657	REV. A
			JY	SIZE	B

Research Develop Innovate

RDI Inc. 333 North Bedford Road, Suite 150, Mount Kisco, NY 10549

THIS DOCUMENT IS OWNED BY, AND THE INFORMATION CONTAINED IN IT IS PROPRIETARY TO, RDI. BY RECEIPT HEREOF THE HOLDER AGREES NOT TO USE THE INFORMATION AND NOT TO DISCLOSE IT TO ANY THIRD PARTY. NOR REPRODUCE THIS DOCUMENT AND WITHOUT THE WRITTEN CONSENT OF RDI. AND AGREES TO RETURN THIS DOCUMENT FORTHWITH UPON REQUEST.