



Product: <u>5220FL</u> ☑

Fire Alarm, #16-2c BC, Shielded, FPLR

## **Product Description**

Fire Alarm Cable, Riser-FPLR, 2-16 AWG solid bare copper conductors with polypropylene insulation, overall Beldfoil® shield, PVC jacket with ripcord

## **Technical Specifications**

### **Product Overview**

Suitable Applications:	Fire Alarm, Monitor/Detection, Circuits: Audio, Control, Initiating, Notification, Noisy Environment

#### **Construction Details**

#### Conductor

Element	Number of Element	Size	Stranding	Material
Conductor(s)	2	16 AWG	Solid	BC - Bare Copper

#### Insulation

Element	Material	Nom. Thickness	Nom. Insulation Diameter	Color Code
Conductor(s)	PP - Polypropylene	0.007 in (0.18 mm)	0.065 in (1.7 mm)	Black, Red

### Outer Shield

Shield Type	Material	Coverage	Drainwire Type
Таре	Bi-Laminate (Alum+Poly)	100%	24 AWG (Solid) TC

## Outer Jacket

Material	Nom. Th	nickness	Nom. Diameter	Ripcord
PVC - Polyvinyl Chloride	0.017 in	(0.43 mm)	0.170 in (4.32 mm)	Yes
Overall Cable Diameter (I	Nominal):	0.170 in (	4.32 mm)	

# **Electrical Characteristics**

### Electricals

Element	Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Nom. Capacitance Cond-to-Other (Conds + Shield)	Max. Current
Conductor(s)	3.9 Ohm/1000ft	65.5 pF/ft (215 pF/m)	118 pF/ft (387 pF/m)	6.3 Amps per conductor @ 25°C

### Voltage

UL Voltage Rating 300 V (FPLR)

### **Mechanical Characteristics**

#### Temperature

UL Temperature	Operating
75°C	-20°C to +75°C

#### Bend Radius

Stationary Min.	Installation Min.	
1.7 in (43 mm)	1.7 in (43 mm)	

Max. Pull Tension: 75 lbs (34 kg)

Bulk Cable Weight:	23 lbs/1000ft		
--------------------	---------------	--	--

#### **Standards and Compliance**

Environmental Suitability:	Indoor - Riser, Indoor
Flammability / Reaction to Fire:	UL 1666 Riser, IEC 60332-1-2
CPR Compliance:	CPR Euroclass: Eca
NEC / UL Compliance:	Article 760, FPLR
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
UK Regulation Compliance:	UKCA Mark
APAC Compliance:	China RoHS II (GB/T 26572-2011)
Plenum Number:	6220FL

#### **History**

Update and Revision:	Revision Number: 0.461 Revision Date: 04-03-2023

#### **Part Numbers**

#### Variants

Item #	Color	UPC
5220FL D151000	Blue	612825158301
5220FL 0021000	Red	612825158318
5220FL 0091000	White	612825158325

#### © 2023 Belden, Inc

#### All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.