


## P295BJ182M500A

P295, Film, Metallized Paper, Automotive Safety, 1800 pF, 20%, 500 VAC (Y1), 1500 VDC, 115°C, Lead Spacing = 15mm



Click here for the 3D model.

Dimensions	
L	18mm MAX
Н	12.5mm MAX
Т	6.5mm MAX
S	15mm +/-0.4mm
LL	30mm +5mm
F	0.8mm +/-0.05mm
G	0.5mm NOM

Packaging Specifications		
Packaging	Bulk, Bag	
Packaging Quantity	400	

General Information	
Series	P295
Dielectric	Metallized Paper
Style	Radial
Features	EMI Safety
RoHS	Yes
Lead	Wire Leads
Safety Class	Y1
Qualifications	ENEC, UL, cUL, CQC, AEC-Q200
AEC-Q200	Yes
THB Performance	No
Component Weight	1.89 g
Miscellaneous	SRF= 37 MHz.

Specifications				
Capacitance	1800 pF			
Capacitance Tolerance	20%			
Voltage AC	500 VAC (Y1)			
Voltage DC	1500 VDC			
Temperature Range	-40/+115°C			
Rated Temperature	115°C			
Dissipation Factor	1.3% 1kHz			
Insulation Resistance	12 GOhms			
Max dV/dt	2000 V/us			

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.