

## Specification Sheet

Part Number: 151-10952



Q Tag, Right Angled, 3.9" x 1.7", For Q18 thru Q30 ties, PA66, White, 50/bag

<b>Article Number</b>	151-10952
<b>Type</b>	QT7040S
<b>Color</b>	White (WH)
<b>Features &amp; Benefits</b>	•Opening on the tag allows the Q Tie to be easily inserted, providing a secure identification solution
<b>Quantity Per</b>	bag

### Product Description

Q-tags are used to identify a cable or a cable bundle and is secured with a Q-tie. The Q-tag's flag design allows the user to quickly read or scan the printed information. The tags can be marked by hand with a marker pen (T82 series) or with a printed adhesive label. HellermannTyton offers a complete printing solution for Q-tags: printers, labels, ribbons, and market leading label design software, TagPrint Pro. Using Q-ties and Q-tags gives users the confidence that cables and cable bundles are safely secured and the text is highly visible.

<b>Short Description</b>	Q Tag, Right Angled, 3.9" x 1.7", For Q18 thru Q30 ties, PA66, White, 50/bag
<b>Global Part Name</b>	QT7040S-PA66-WH
<b>Length L (Metric)</b>	88.0
<b>Fixation Method</b>	Others
<b>Variant</b>	Other
<b>Width W (Imperial)</b>	3.46
<b>Width W (Metric)</b>	88.0
<b>Thickness T (Imperial)</b>	0.055
<b>Thickness T (Metric)</b>	1.4
<b>Height H (Imperial)</b>	1.65
<b>Height H (Metric)</b>	42.0
<b>Cable Tie Width Max (Imperial)</b>	0.14
<b>Cable Tie Width Max (Metric)</b>	3.6
<b>Material</b>	Polyamide 6.6 (PA66)
<b>Material Shortcut</b>	PA66

<b>Flammability</b>	UL 94 V2
<b>Halogen free</b>	Yes
<b>Operating Temperature (Metric)</b>	-40°F to +185°F (-40°C to +85°C)
<b>Reach Complaint(Article 33)</b>	Yes
<b>ROHS Complaint</b>	Yes
<b>Package Quantity(Imperial)</b>	50
<b>Package Quantity (Metric)</b>	50
<b>Customs Number</b>	3926909988
<b>Content Unit(BMEcat)</b>	pcs.