

MATERIAL: HOUSING: SHELL: CONTACT:

THERMOPLASTIC POLYESTER, UL94V-0 STEEL, TIN PLATED COPPER ALLOY, 30µ GOLD PLATED

OPERATING TEMPERATURE:


POWER/CO-AX CONTACT RATING: 20A (CURRENT) (IF PRESENT) SIGNAL CONTACT CURRENT RATING: 5A PER CONTACT

SIGNAL CONTACT RESISTANCE:  $10m\Omega$  MAX.

INSULATOR RESISTANCE: DIELECTRIC WITHSTANDING VOLTAGE: 5000MΩ min.

-55°C ~ 125°C

1000V AC rms



**ISSUE NUMBER** 

(1)

ORIGINAL

				SW REFERENCE NO.: 630 COMBO ASSEMBLY				
		COMBINATION	D-SUB	DRAWN: C.B		DATE: JAN. 01/2019		
				CHECKED:		DATE:		
YOUR CONN		EDAC INC	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	SCALE: (IN C.A.D. ?	l:1)	SHEET 1 C	F 2	
		TORONTO, ONTARIO CANADA		DRAWING NUMBER: 630-21W4		4650-2T5	ISSUE	
	OUR CONNECTION TO	QUALITY & SERVICE		PART NUMBER:	630-21W4	4650-2T5	1	



12.50

THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

