



LAYOUT SHOWN AS EXAMPLE

Keying Shown as example

**CHARACTERISTICS**

- Standard : Based on MIL-DTL-38999 Series III
- Shell Material : Aluminium
- Shell Plating : Black Zinc Nickel
- Insulator : Thermoplastic
- Contacts : Copper Alloy
- Seals & Grommet : Silicon Elastomer
- Contact Plating : Gold over copper Alloy 0.8µm minimum
- Durability : 500 Mating cycles
- Delivered without Souriau contacts
- Temperature Range : -65°C to +175°C
- Salt Spray : 500 hours

| Connector dimension |          |
|---------------------|----------|
| Dim                 | Nominal  |
| ØS                  | 35.7 Max |
| Z                   | 31 Max   |
| VV THREAD           | M25x1-6g |

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)

| Country | Jurisdiction & Control List |
|---------|-----------------------------|
| FR      | Not Listed                  |

**PN: 8D517Z20SCL**

|              |            |                          |                         |
|--------------|------------|--------------------------|-------------------------|
| A            | 18-10-2016 | First Release            |                         |
| ISS          | DATE       | Latest modification - by | MOD N°                  |
| Designed By: |            | Date:                    | <b>CUSTOMER DRAWING</b> |

|              |                                 |  |  |
|--------------|---------------------------------|--|--|
| <b>TITLE</b> | <b>Aluminium Plug 8D series</b> |  |  |
|--------------|---------------------------------|--|--|

|       |  |                                |                 |
|-------|--|--------------------------------|-----------------|
| SCALE |  | General linear Tolerances: ±-- | NPRDS / PROJECT |
| NA    |  |                                | <b>859</b>      |

|                |                        |   |
|----------------|------------------------|---|
| <b>SOURIAU</b> | <b>WWW.SOURIAU.COM</b> | This document is the property of SOURIAU it must not be reproduced or communicated without permission |
|----------------|------------------------|---|

|           |                                     |            |
|-----------|-------------------------------------|------------|
| FORMAT    | <b>SOURIAU DRG N° 8D517Z20SCL-C</b> | SHEET      |
| <b>A3</b> |                                     | <b>1/2</b> |

|                |                         |                   |   |    |   |    |   |   |   |                                    |
|----------------|-------------------------|-------------------|---|----|---|----|---|---|---|------------------------------------|
| BASIC SERIES:  | 8D                      | 5                 | - | 17 | Z | 20 | S | C | L | Delivered W/O Contacts             |
| SHELL TYPE :   | Plug with RFI Shielding |                   |   |    |   |    |   |   |   | ORIENTATION : C                    |
| CONTACT TYPE : | Standard Crimp Contact  |                   |   |    |   |    |   |   |   | CONTACT TYPE : SOCKET(500 Matings) |
| SHELL SIZE :   | 17                      |                   |   |    |   |    |   |   |   | CONTACT LAYOUT : 17-20             |
| PLATING :      | Z =                     | Black Zinc Nickel |   |    |   |    |   |   |   |                                    |

Contact Layout

20\*



4#12  
16#22D

| 17-20 |       |       |
|-------|-------|-------|
| Ctc   | X     | Y     |
| A     | 0     | 5.51  |
| B     | 3.17  | 0     |
| C     | 0     | -5.51 |
| D     | -3.17 | 0     |
| 1     | 4.16  | 7.06  |
| 2     | 4.29  | 4.29  |
| 3     | 7.11  | 4.03  |
| 4     | 8.05  | 1.4   |
| 5     | 8.05  | -1.4  |
| 6     | 7.11  | -4.03 |
| 7     | 4.29  | -4.29 |
| 8     | 4.16  | -7.06 |
| 9     | -4.16 | -7.06 |
| 10    | -4.29 | -4.29 |
| 11    | -7.11 | -4.03 |
| 12    | -8.05 | -1.4  |
| 13    | -8.05 | 1.4   |
| 14    | -7.11 | 4.03  |
| 15    | -4.29 | 4.29  |
| 16    | -4.16 | 7.06  |

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)

| Country | Jurisdiction & Control List |
|---------|-----------------------------|
| FR      | Not Listed                  |

PN: 8D517Z20SCL

|                |                              |                            |   |
|----------------|------------------------------|----------------------------|---|
| A              | 18-10-2016                   | First Release              |   |
| ISS            | DATE                         | Latest modification - by   | MOD N°  |
| Designed By:   |                              | Date:                      | <b>CUSTOMER DRAWING</b>   |
| <b>TITLE</b>   | Aluminium Plug 8D series     |                            |   |
| SCALE          |                              | General linear Tolerances: | NPRDS / PROJECT   |
| NA             |                              | ±--                        | <b>859</b>  |
| <b>SOURIAU</b> | WWW.SOURIAU.COM              |                            | This document is the property of SOURIAU it must not be reproduced or communicated without permission |
| FORMAT         | SOURIAU DRG N° 8D517Z20SCL-C |                            | SHEET 2/2   |