ב בו בי		D	0	B		
Z       Image: state						
5			LAYOUT SHOWN AS EXAM	1PLE		
	Keying Shown as example					
CHARACTERISTICS	Connector dimension					
-Standard : Based on MIL-DTL-38999 Series III	Dim Nominal ØS 41.7 Max					
-Shell Material : Aluminium -Shell Plating : Olive drab Cadmium -Insulator : Thermoplastic -Contacts : Copper Alloy	Z 31 Max VV THREAD M31x1-6g		SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)			
-Seals & Grommet : Silicon Elastomer			Country     Jurisdiction & Control List       FR     Not Listed			
-Contact Plating       : Gold over copper Alloy 0.8μm minimum         -Durability       : 500 Mating cycles						
-Delivered with Souriau contacts and Accessories			PN: 8D521W4	13E		
-Temperature Range : -65°C to +175°C		A 10-10-2016	First Release			
-Salt Spray : 500 hours 		ISS DATE	Latest modification - by		MOD N°	
		Designed By:				
		IIILE	TITLE Aluminium Plug 8D series			
	41 S E	SCALE -	General linear Tolerances:	NPRDS / PROJECT <b>859</b>		
SHELL TYPE : Plug with RFI Shielding		NA		This document is the prope	erty of	
CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 21	ITACT TYPE : Standard Crimp Contact ORIENTATION : E LL SIZE : 21 CONTACT TYPE : SOCKET(500 Matings)			SOURIAU WWW.SOURIAU.COM it must not be reproduced or communicated without permissi		
PLATING : W = Olive drab Cadmium	CONTACT LAYOUT				SHEET	
		A3				
		A A A	8D521W41		1/2	

	Т	۵	п –	m		· · · ·
		Contact Layout			<u>.</u>	·
4	<	31° 23 33° 41'				
		1         1				
ى	size no. cont	Insert arrangement 21-41 ber of Size Service Contact Superseder tacts contacts rating location 11 20 I All MS20055-4				
						SOURIAU shall not be liable for ar due to a use of the Products w
2						the Specifications issued by either of (professional recommenda Count FR PN: 8D521
					A 10-10-20 ISS DATE Designed By:	116 First Release
-					SCALE NA	Alumir General linear Tolerances: ±
					FORMAT A3	SOURIAU 8D521W
	Н	G	F F	E	D	C

