	T Q T	m	, c	-	0				
4	Z Peaulit M Peaulit M								-
ω		A Constant of the second secon			LAYOUT SHOWN	AS EXAMPLE			
	Кеуі	ing Shown as example							
(CHARACTERISTICS	Connector dimension							
	-Standard : Based on MIL-DTL-38999 Series III	Dim Nominal ØS 41.7 Max	_						+
	-Shell Material : Aluminium -Shell Plating : Olive drab Cadmium	Z 31 Max VV THREAD M31x1-6g		SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with					
	-Insulator : Thermoplastic	WY THINKAD WISTAT-05			the Specifications issued by eit	her of the Parties or by	a third party		
	-Contacts : Copper Alloy				(professional recomm	endation, technical not	ice.)		
.	-Seals & Grommet : Silicon Elastomer						tion & Control List		
	-Contact Plating : Gold over copper Alloy 0.8µm minimum					FR	Not Listed		
	-Durability : 500 Mating cycles				PN: 8D52	1W72SNL			
	-Delivered without Souriau contacts		F						
	-Temperature Range : -65°C to +175°C -Salt Spray : 500 hours			A 10-10-2016	First Release				
			-	ISS DATE	Latest modification - by			MOD N°	,
			-	Designed By:	Date:		CUSTOMER DRAWING		_
			TITLE		Aluminium Plug 8D series		series		
	BASIC SERIES: 8D 5 - 21 W 72 S	NL	-	SCALE	General lin	near	NPRDS / PROJECT		
-				NA	-{		859		
-	SHELL TYPE : Plug with RFI Shielding		W/O Contacts				This document is the prope	erty of	
-	CONTACT TYPE : Standard Crimp Contact		ENTATION : N	SOURIAU	WWW.SOURIA	U.COM	SOURIAU it must not be reproduce		
-	SHELL SIZE : 21	CONTACT TYPE : SOCKET	(500 Matings)				communicated without per	mission	
F	PLATING : W = Olive drab Cadmium	CONTACT LA	AYOUT : 21-72			AU DRG N°		SHEET	
				A3	8D521	W72SNL-C		1/2	

	Ŧ	۵	г	т	D	0
		Contact Layout				
4						
		2#4 Power 6#16				
		21-72]			
	Ctc	ХҮ				
	A	0 6.19	-			
	В	8.5 4.3	-			
ယ	C D	6.25 0 8.5 -4.3	-			
	E	0 -6.19	-			
	F	-8.5 -4.3	1			
	G	-6.25 0]			
	Н	-8.5 4.3				
	l					
						SOURIAU shall not be liable for any due to a use of the Products wh the Specifications issued by either of (professional recommendat Countr
N						PN: 8D521W
					A 10-10-20	16 First Release
					ISS DATE	
					Designed By:	Date:
					TITLE	Alumin
<u> </u>					SCALE NA	General linear Tolerances: ±
					SOURIA	U WWW.SOURIAU.C
					FORMAT	SOURIAU
					A3	8D521W7
L	Н	G	F	E	D	С

			4		
			3		
any non-conformit which does not co or of the Parties or b dation, technical no intry Jurisd R W72SNL	mply with by a third party		2		
	CUSTOMER DRAWING	MOD N°			
ninium Plug 8D series					
	859		1		
.COM This document is the property of SOURIAU it must not be reproduced or communicated without permission					
		SHEET 2/2			
V72SNL-C	A	212	J		
В	A A				

Β