


### DAISY-7X1-O-D

~25 + 70° oval beam. Variant with diffused lenses.

#### SPECIFICATION:

Dimensions	279.5 x 39.6 mm
Height	20.3 mm
Fastening	pin, screw, clips
ROHS compliant	yes ⓘ



#### MATERIALS:


Component	Type	Material	Colour	Finish
C17540_DAISY-7X1-O-D	Linear lens	PMMA	milky	
C18409_DAISY-7X1-SHD-MET-MATT	Shade	PC	metal	matt
C18167_DAISY-7X1-SHD-MET	Shade	PC	metal	gloss
C17225_DAISY-7X1-SHD-WHT-MATT	Shade	PC	white	matt
C17051_DAISY-7X1-SHD-MATT	Shade	PC	black	matt
C16876_DAISY-7X1-SHD-WHT	Shade	PC	white	gloss
C16872_DAISY-7X1-SHD	Shade	PC	black	gloss

#### ORDERING INFORMATION:

##### Quantities for one set:













Linear lens	1
Shade	1

Component		Qty in box	MOQ	MPQ	Box weight (kg)
C17540_DAISY-7X1-O-D	Linear lens	312	192	24	7.0
» Box size: 400 x 300 x 300 mm					
C18167_DAISY-7X1-SHD-MET	Shade	156	192	24	7.0
» Box size: 595 x 360 x 230 mm					
C17051_DAISY-7X1-SHD-MATT	Shade	156	192	24	7.3
» Box size: 595 x 360 x 230 mm					
C18409_DAISY-7X1-SHD-MET-MATT	Shade	156	192	24	7.0
» Box size: 595 x 360 x 230 mm					
C17225_DAISY-7X1-SHD-WHT-MATT	Shade	156	192	24	7.6
» Box size: 595 x 360 x 230 mm					
C16872_DAISY-7X1-SHD	Shade	156	192	24	7.1
» Box size: 595 x 360 x 230 mm					
C16876_DAISY-7X1-SHD-WHT	Shade	156	192	24	7.6
» Box size: 595 x 360 x 230 mm					



See also our general installation guide: [www.ledil.com/installation\\_guide](http://www.ledil.com/installation_guide)



### OPTICAL RESULTS (MEASURED):

 <p>LED LED Line SMD L28W2 TW Module 20mm 2800Lm Daisy 7</p> <p>FWHM / FWTM 73.0 + 40.0° / 97.0 + 81.0°</p> <p>Efficiency 64 %</p> <p>Peak intensity 0.7 cd/lm</p> <p>LEDs/each optic 2</p> <p>Light colour Tunable White</p> <p>Required components: C17051_DAISY-7X1-SHD-MATT</p>		
 <p>LED LED Line SMD L28W2 White Module 20mm 2800Lm Daisy 7</p> <p>FWHM / FWTM 72.0 + 40.0° / 97.0 + 80.0°</p> <p>Efficiency 64 %</p> <p>Peak intensity 0.7 cd/lm</p> <p>LEDs/each optic 2</p> <p>Light colour White</p> <p>Required components: C17051_DAISY-7X1-SHD-MATT</p>		
 <p>LED LUXEON HL2Z</p> <p>FWHM / FWTM 72.0 + 40.0° / 97.0 + 81.0°</p> <p>Efficiency 66 %</p> <p>Peak intensity 0.7 cd/lm</p> <p>LEDs/each optic 2</p> <p>Light colour White</p> <p>Required components: C17051_DAISY-7X1-SHD-MATT</p>		
 <p>Your solutions</p> <p>LED LinLED 280x28mm 1600lm 840 4C 21V DAISY 7x1(ZT25)</p> <p>FWHM / FWTM 75.0 + 43.0° / 97.0 + 83.0°</p> <p>Efficiency 66 %</p> <p>Peak intensity 0.7 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components: C16872_DAISY-7X1-SHD</p>		



### OPTICAL RESULTS (MEASURED):





**LED** NCSxE17A  
**FWHM / FWTM** 75.0 + 41.0° / 96.0 + 82.0°  
**Efficiency** 64 %  
**Peak intensity** 0.7 cd/lm  
**LEDs/each optic** 1  
**Light colour** White  
**Required components:**  
 C17051\_DAISY-7X1-SHD-MATT





**LED** LH231B  
**FWHM / FWTM** 69.0 + 46.0° / 101.0 + 94.0°  
**Efficiency** 84 %  
**Peak intensity** 0.8 cd/lm  
**LEDs/each optic** 2  
**Light colour** White  
**Required components:**  
 C17533\_DAISY-7X1-SHD-MET-MATT



**LED** LH231B  
**FWHM / FWTM** 70.0 + 43.0° / 99.0 + 83.0°  
**Efficiency** 65 %  
**Peak intensity** 0.7 cd/lm  
**LEDs/each optic** 2  
**Light colour** White  
**Required components:**  
 C17051\_DAISY-7X1-SHD-MATT




**LED** LH231B  
**FWHM / FWTM** 72.0 + 46.0° / 104.0 + 100.0°  
**Efficiency** 86 %  
**Peak intensity** 0.7 cd/lm  
**LEDs/each optic** 2  
**Light colour** White  
**Required components:**  
 C17225\_DAISY-7X1-SHD-WHT-MATT



### OPTICAL RESULTS (MEASURED):


#### SAMSUNG

LED LH231B  
 FWHM / FWTM 70.0 + 43.0° / 99.0 + 84.0°  
 Efficiency 65 %  
 Peak intensity 0.7 cd/lm  
 LEDs/each optic 2  
 Light colour White  
 Required components:  
 C16872\_DAISSY-7X1-SHD





#### SAMSUNG

LED LH231B  
 FWHM / FWTM 68.0 + 47.0° / 100.0 + 93.0°  
 Efficiency 86 %  
 Peak intensity 0.8 cd/lm  
 LEDs/each optic 2  
 Light colour White  
 Required components:  
 C18167\_DAISSY-7X1-SHD-MET



#### SAMSUNG


LED LH231B  
 FWHM / FWTM 72.0 + 47.0° / 104.0 + 100.0°  
 Efficiency 85 %  
 Peak intensity 0.7 cd/lm  
 LEDs/each optic 2  
 Light colour White  
 Required components:  
 C16876\_DAISSY-7X1-SHD-WHT



### OPTICAL RESULTS (SIMULATED):


#### LUMILEDS

LED LUXEON 2835 Line  
FWHM / FWTM 68.0 + 41.0° / 96.0 + 77.0°  
Efficiency 74 %  
Peak intensity 0.9 cd/lm  
LEDs/each optic 2  
Light colour White  
Required components:  
C16872\_DAISSY-7X1-SHD




#### SAMSUNG

LED LM28xB Series  
FWHM / FWTM 71.0 + 46.0° / 96.0 + 80.0°  
Efficiency 74 %  
Peak intensity 0.8 cd/lm  
LEDs/each optic 2  
Light colour White  
Required components:  
C17051\_DAISSY-7X1-SHD-MATT



#### SAMSUNG

LED LM28xB Series  
FWHM / FWTM 70.0 + 44.0° / 96.0 + 80.0°  
Efficiency 74 %  
Peak intensity 0.8 cd/lm  
LEDs/each optic 2  
Light colour White  
Required components:  
C16872\_DAISSY-7X1-SHD



### GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

### MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

### PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

#### LEDiL Oy

Joensuunkatu 13  
FI-24240 SALO  
Finland

#### LEDiL Inc.

228 West Page Street  
Suite D  
Sycamore IL 60178  
USA

#### Ledil Optics Technology (Shenzhen) Co., Ltd.

# 405 , Block B  
Casic Motor Building  
Shenzhen 518057  
P.R.CHINA

#### Local sales and technical support

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)

#### Shipping locations

Salo, Finland  
Hong Kong, China

#### Distribution Partners

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)