


FLLE2032APDI

Aliases (LLE2032APDI)

KEMET, FLLE2-P, EMI/RFI Filters, Noise Suppression, 300 VAC, 300 V, 32 A, 91x51x45mm



General Information Series FLLE2-P Style **Chassis Mount** Description Single Phase, Chassis Mount Filters Single Phase Features Phase Single-phase RoHS Yes Qualifications IEC/EN 60939, UL, CSA Threaded Studs M4 **Terminal Type**

Specifications	
Voltage AC	300 VAC
Voltage DC	300 VDC
Rated Frequency	50-60 Hz
Rated Current	32 A
Rated Temperature	40°C
Temperature Range	-25/+100°C
Climate Category	25/100/21
Leakage Current	0.79 mA (MAX)
Test Voltage DC (P/N to E)	2250 VDC
Test Voltage DC (P to N)	1300 VDC

Click here for the 3D model.

Dimensions		
L	91mm MIN	
W	51mm MIN	
Н	45mm MIN	

Packaging Specifications	
Packaging	Bulk
Packaging Quantity	1
Component Weight	415 g

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.