

Controller - RFC 460R PN 3TX - 2700784

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



High-availability Remote Field Controller with redundancy function, 3 x 10/100 Ethernet, PROFINET controller, IP20 protection, plug-in parameterization memory

Product Description

High-availability Remote Field Controller for PROFINET networks


When it comes to high-availability, distributed, and modular automation, Remote Field Controllers (RFCs) with IEC 61131 control intelligence, redundancy technology, and network connection are the ideal solution. Thanks to the integrated fiber optic-based redundancy function, you can reduce system downtimes, work cost-effectively, and also avoid potential hazards, e.g., in tunnels or at airports.

Your advantages

- ✓ The RFC 460R PN 3TX features:
- ✓ Fast startup and automatic configuration of all redundancy functions, thanks to AutoSync technology
- ✓ Uninterrupted process in the event of failure or when a controller is replaced
- ✓ Optimum device integration, thanks to PROFINET standards; redundancy for your future-proof Ethernet network
- ✓ High-resolution display for displaying status and error messages in plain text
- ✓ Uninterrupted visualization - thanks to redundancy-capable OPC server
- ✓ A distance of up to 80 km between the controllers via fiber optics; cost-optimized thanks to plug-in SFP modules



Key Commercial Data

Packing unit	1 pc
GTIN	 4 046356 640589
GTIN	4046356640589

Technical data

Dimensions

Width	124 mm
Height	185 mm
Depth	190 mm

Ambient conditions

Degree of protection	IP20
----------------------	------

Controller - RFC 460R PN 3TX - 2700784

Technical data

Ambient conditions

Ambient temperature (operation)	0 °C ... 55 °C (from 45°C only with fan module)
Ambient temperature (storage/transport)	-25 °C ... 70 °C
Permissible humidity (operation)	5 % ... 90 % (non-condensing)
Permissible humidity (storage/transport)	5 % ... 90 % (non-condensing)
Air pressure (operation)	80 kPa ... 106 kPa (up to 2000 m above sea level)
Air pressure (storage/transport)	66 kPa ... 108 kPa (up to 3000 m above sea level)
Shock	25g, Criterion 1, according to IEC 60068-2-27
Vibration (operation)	1g, Criterion 1, according to IEC 60068-2-6

Control system

Engineering tool	PC WORX
Programming languages supported	Programming in acc. with IEC 61131-3
Diagnostics tool	DIAG+, version 2.00 or higher

IEC 61131 runtime system

Engineering tool	PC WORX
Program memory	typ. 8 Mbyte
Mass storage	16 Mbyte
Retentive mass storage	120 kByte (NVRAM)
Number of control tasks	1
Realtime clock	Integrated (battery backup)

Data interfaces

Interface	Ethernet
Number	3
Connection method	RJ45 socket
Transmission speed	10/100 Mbps
Interface	Synchronization interface
Number	1
Connection method	SFP port
Transmission speed	1 Gbps
Interface	USB 2.0
Number	2
Connection method	USB type A, socket

PROFINET

Device function	PROFINET-Controller
Specification	Version 1.1
Update rate	min. 1 ms

Power supply

Power supply connection	Screw terminal blocks, plug-in
Typical current consumption	1 A

Controller - RFC 460R PN 3TX - 2700784

Technical data

Power supply

Supply voltage	24 V DC
Supply voltage range	19.2 V DC ... 30 V DC (including ripple)
Power dissipation	max. 24 W

Mechanical design

Format	124 x 185 x 190 mm (W x H x D without fan)
	124 x 210 x 190 mm (W x H x D with fan)
Weight	1870 g
Note on weight specifications	without fan module
Weight	2010 g
Note on weight specifications	with fan module
Diagnostics display	yes
Controller redundancy	yes
Safety function	No

General data

Processor	Intel® Celeron® 927 UE 1.5 GHz
-----------	--------------------------------

Standards and Regulations

Vibration (storage/transport)	1g, Criterion 1, according to IEC 60068-2-6
Shock	25g, Criterion 1, according to IEC 60068-2-27
Vibration (operation)	1g, Criterion 1, according to IEC 60068-2-6

Environmental Product Compliance

REACH SVHC	1,2-dimethoxyethane, ethylene glycol dimethyl ether (EGDME) 110-71-4
	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Approvals

Approvals

Approvals






UL Listed / cUL Listed / EAC / EAC / cULus Listed

Ex Approvals

Approval details

Controller - RFC 460R PN 3TX - 2700784

Approvals

UL Listed		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	FILE E 140324
cUL Listed		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	FILE E 140324
EAC			EAC-Zulassung
EAC			RU *- DE.A*30.B.00238
cULus Listed			

Phoenix Contact 2019 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>