
THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MASTER.





ISSUE NUMBER

ORIGINAL

1









HOUSING: PBT, UL94V-0

WIRE-HOUSING SEAL: SILICON RUBBER

SPECIFICATIONS:

PITCH: 2.0MM

RATED VOLTAGE: 250V

2. 3. RATED CURRENT: 2A MAX


WITHSTAND VOLTAGE: AC1000V R.M.S. 5. CONTACT RESISTANCE: 10 mOHMS MAX

INSULATION RESISTANCE:

1000 MOHMS MIN/DC 500V

TEMPERATURE RANGE: -40°C ~ +105°C 8. WATERPROOF GRADE: TESTED AND

CERTIFIED TO IP67



| ITEM NO. | DESCRIPTION | QTY. |
|----------|-------------------------|------|
| 1 | 566-004-000-810_Housing | 1 |
| 2 | 566-004-000-810_Rubber | 1 |

566 SERIES 4 SOCKET WATERPROOF CONNECTOR

ACAD REFERENCE NO. 566 ASSEMBLY DRAWN:R.STA.MONICA DATE: NOV.02/10 CHECKED: DATE: SCALE: NOT TO SCALE SHEET 1 OF 1 DRAWING NUMBER ISSUE

EDAC INC TORONTO, ONTARIO

CANADA

YOUR CONNECTION TO QUALITY & SERVICE

ARE THE PROPERTY OF EDAC INC., AND SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

THESE DRAWINGS AND SPECIFICATIONS

566-004-000-810



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2002/95/EC AND 2002/96/EC FOR RoHS COMPLIANCY