

ATGBICS E10GSFPSRX Intel Compatible Transceiver SFP+ 10GBase-SR (850nm, MMF, 300m, DOM) network transceiver module Fiber optic 10000 Mbit/s SFP+



Brand : ATGBICS

Product code: E10GSFPSRX-C

Product name : E10GSFPSRX Intel Compatible Transceiver SFP+ 10GBase-SR (850nm, MMF, 300m, DOM)

Intel Compatible Transceiver SFP+ 10GBase-SR 850nm MMF 300m DOM

[ATGBICS E10GSFPSRX Intel Compatible Transceiver SFP+ 10GBase-SR \(850nm, MMF, 300m, DOM\) network transceiver module Fiber optic 10000 Mbit/s SFP+:](#)

ATGBICS E10GSFPSRX 10GBase-SR supports a distance of up to 300m over multi-mode fibre (MMF) using a wavelength of 850nm via an LC connector. Digital optical monitoring (DOM) support is also present enabling real-time monitoring of the parameters of the fibre optic transceiver. Our product is built to the exact specification of Intel E10GSFPSRX= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards.

Performance		Features	
SFP transceiver type *	Fiber optic	Easy to install	✓
Maximum data transfer rate *	10000 Mbit/s	Country of origin	United Kingdom
Interface type *	SFP+	Brand compatibility	Intel
Single-mode fiber (SMF) supported	✗	Certification	CE, FCC, ROHS
Multi-mode fiber (MMF) supported	✓	Power	
Fiber optic connector	LC	Input voltage	3.3 V
SFP transceiver standard	SR	Maximum voltage	3.5 V
Maximum transfer distance	300 m	Maximum current	1 A
Wavelength	850 nm	Operational conditions	
Coarse Wavelength Division Multiplexing (CWDM)	✗	Maximum operating temperature	70 °C
Ethernet LAN	✓	Operating temperature (T-T)	0 - 70 °C
Ethernet interface type	10 Gigabit Ethernet	Storage temperature (T-T)	-40 - 85 °C
Networking standards	IEEE 802.3ae	Operating relative humidity (H-H)	0 - 95%
Fiber ethernet cabling technology	10GBASE-SR	Storage relative humidity (H-H)	0 - 95%
Digital Diagnostics Monitoring (DDM)	✓	Weight & dimensions	
Features		Width	13.4 mm
Product colour	Silver	Depth	56.5 mm
Housing material	Steel	Height	8.5 mm
Plug and Play	✓	Weight	19 g
Hot-Plug support	✓	Packaging data	
Hot-swap	✓	Number of products included	1 pc(s)
		Technical details	
		Sustainability compliance	✓
		Sustainability certificates	RoHS

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 14-OCT-2021. Prints or copies of Information are only valid on the printed Publication date