

Product Search Data Sheet

Note: This datasheet may be out of date. Please download the latest datasheet of GJM0225C1E4R6BB01# from the official website of Murata Manufacturing Co., Ltd.

"#" indicates a package specification code.

0.09mg

http://www.murata.com/en-us/products/productdetail?partno=GJM0225C1E4R6BB01%23

References

Specifications

180Embossed Tape

Packaging

Mass (typ.)

1 piece

L

GJM0225C1E4R6BB01L




< List of part numbers with package codes > GJM0225C1E4R6BB01L

Applications

Please be sure to read and comply with
these "Precautions for use."
Consumer equipment, Industrial
Equipment, Mobile Electronics, Medical
equipment [GHTF A/B/C] except for
implant equipment,Automotive
infotainment/comfort equipment
Please refer to Our Website and
specifications, etc. for information about
the performance, functions, quality,
management, and safety required for
the above applications, and use
Products after confirming the
performance and reliability of the actual
Product.

Appearance & Shape





1 of 2

Standard

Packing Quantity

40000

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





GJM0225C1E4R6BB01L

Note: This datasheet may be out of date. Please download the latest datasheet of GJM0225C1E4R6BB01# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=GJM0225C1E4R6BB01%23

"#" indicates a package specification code.



Specifications

Length	0.4±0.02mm
Width	0.2±0.02mm
Thickness	0.2±0.02mm
Capacitance	4.6pF ±0.1pF
Distance between external terminals g	0.13mm min.
External terminal size e	0.07 to 0.14mm
Operating Temperature Range	-55℃ to 125℃
Rated Voltage	25Vdc
Size code in inch(mm)	01005 (0402M)
TC	0±30ppm/°C
Temperature characteristics (complied standard)	C0G(EIA)
Temperature range of temperature characteristics	25℃ to 125℃

2 of 2

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.