



Tripp Lite 1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

Protect It! 6-Outlet Surge Protector, 6-ft. Cord, 1080 Joules, Ethernet Protection, Safety Covers

MODEL NUMBER: TLP66NET







Highlights

- 6 outlets / 6-ft cord
- 1080 joule rating
- Ethernet surge protection

Package Includes

- TLP66NET
- 6-ft. network cable
- Instruction manual with warranty information

Description

Tripp Lite's TLP66NET surge suppressor has 6 outlets, a 6-ft. cord and diagnostic LEDs. The unit has a surge suppression rating of 1080 joules to handle the strongest surges. Built-in RJ45 jacks prevent surges from damaging your network equipment (6-ft network cable included). \$25,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only).

Features

- 6 outlets with integrated child safety covers
- 6ft cord
- Built-in RJ45 jacks prevent surges from damaging your network equipment (6ft. network cable included)
- Surge suppression rating: 1080 joules
- EMI/RFI noise filtering
- Can accommodate up to 2 transformers without blocking remaining outlets
- Diagnostic LEDs indicate protection present & ground present
- Keyhole supports for wall mounting
- Lighted power switch
- \$25,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only)
- Automatic shutoff permanently cuts power to outlets if protection circuit is incapacitated, preventing equipment damage and indicating replacement is required

Specifications

OVERVIEW



Tripp Lite 1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

UPC Code	037332159700	
OUTPUT		
Frequency Compatibility	60 Hz	
Output (Watts)	1800	
Output Receptacles	(6) 5-15R	
Circuit Breaker (amps)	15	
Overload Protection	15A resettable illuminated combo switch / circuit breaker	
Transformer Accommodation	(4) Yes	
Outlet Orientation	Block style with two rows of 3 outlets	
Right-Angle Outlets	No	
INPUT		
Nominal Input Voltage(s) Supported	120V AC	
Recommended Electrical Service	120V (110-125V)	
Input Cord Gauge Type	14 gauge; SJT	
Voltage Compatibility (VAC)	120	
Maximum Surge Amps	72000	
Input Plug Type	NEMA 5-15P	
Input Cord Length (ft.)	6	
Right-Angle Plug	No	
Input Cord Length (m)	1.83	
Integrated Cord Clip	No	
USER INTERFACE, ALERTS & CONTROLS		
Diagnostic LED(s)	Yes	
Switches	Combination AC circuit breaker and 2-position red illuminated on/off power switch	
Diagnostic LED Details	Built-in LEDs confirm suppressor "protection present" (green) and "grounded" (red) status	
SURGE / NOISE SUPPRESSION		
AC Suppression Joule Rating	1080	
AC Suppression Response Time	< 1 ns	
Protection Modes	Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression	
Clamping Voltage (RMS)	150	
UL1449 Let Through Rating	400v	
EMI / RFI Filtering	Up to 40 dB	
Auto Shut-Off	Yes	



DATALINE SURGE SUPPRESSION		
Telephone/DSL Protection	No	
Cable (Coax) Protection	No	
Network (Ethernet) Protection	Yes	
PHYSICAL		
Shipping Dimensions (hwd / in.)	11.10 x 2.00 x 7.20	
Shipping Dimensions (hwd / cm)	28.19 x 5.08 x 18.29	
Shipping Weight (lbs.)	1.90	
Shipping Weight (kg)	0.86	
Unit Dimensions (hwd / in.)	1.5 x 4.23 x 8.29	
Unit Dimensions (hwd / cm)	3.81 x 10.74 x 21.06	
Unit Weight (Ibs.)	1.32	
Unit Weight (kg)	0.60	
Material of Construction	Plastic	
Integrated Keyhole Mounting Slots	Yes	
Housing Color	Light Gray	
Receptacle Color	Gray	
Color (AC Line Cord)	Light Gray	
Color	Light Gray	
Outlets Measurement (Center to Center)	Distance between standard outlets = 28.5; Distance between standard outlet and transformer outlet = 48.5mm	
Keyhole Slot Mounting Measurement (Center to Center)	119mm	
Anti-Microbial Protected	No	
CERTIFICATIONS		
UL1449 3rd Edition (AC Suppression)	UL1449 3rd Edition	
UL1363 (Power Tap)	UL1363	
Canada	cUL	
Industry Canada (Communications)	Industry Canada	
Approvals	Exceeds IEEE 587 category A&B specifications	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	



Connected Equipment Insurance (U.S., Canada & Puerto Rico)

\$25,000 Ultimate Lifetime Insurance

© 2019 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies