




US24-15MM-15MM-F

Ruland US24-15MM-15MM-F, 15mm x 15mm Single Universal Joint, Friction Bearing, Steel, 38.0mm OD, 108.0mm Length





Description

Ruland US24-15MM-15MM-F is a single cardan friction bearing universal joint with 15mm x 15mm bores, 38.0mm OD, and 108.0mm length. It is ideal for applications with space constraints and has higher torque capacity than equivalently sized double universal joints. This plain bearing universal joint is comprised of pins and blocks that are precision machined, selectively heat treated, and ground for high strength, accuracy, and wear resistance. The combination of these components with precision ground and hardened yoke ears allow for a longer lifespan, increased performance in demanding applications, and greater angular misalignment of up to 45° when compared to commodity style single universal joints. US24-15MM-15MM-F is made from high grade alloy steel for durability and high strength. It can be combined with boot UBOOT24/38-NI-KIT to protect the joint from unwanted contaminants such as dust or water and self lubricate reducing maintenance time. This single cardan universal joint is manufactured in the USA by Belden Universal for strict control of processes.

Product Specifications

1
nm
5 mm / -0.000 mm
ım
3 Nm
n Universal
PLATE No. 1200-2
933221
810
for a particular application.
known to the State of re information go to