ATGBICS XBR-000285 Brocade Compatible Transceiver QSFP+ 4X32GBASE-FC (1310nm, MMF, 2km, DOM)

Brand : ATGBICS

Product code: XBR-000285-C

Product name : XBR-000285 Brocade Compatible Transceiver QSFP+ 4X32GBASE-FC (1310nm, MMF, 2km, DOM)

XBR-000285 Brocade Compatible Transceiver QSFP+ 4X32GBASE-FC (1310nm, MMF, 2km, DOM)

ATGBICS XBR-000285 Brocade Compatible Transceiver QSFP+ 4X32GBASE-FC (1310nm, MMF, 2km, DOM):

ATGBICS XBR-000285 4X32GBASE-FC supports a distance of up to 2km over multi-mode fibre (MMF) using a wavelength of 1310nm via an MPO connector. Digital optical monitoring (DOM) support is also present enabling real-time monitoring of the parameters of the fibre optic transceiver. Our product meets the specification of XBR-000285= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards. 4x32G FC QSFP+.





Performance		Features	
SFP transceiver type *	Fiber optic	Certification	CE, FCC, RoHS
Maximum data transfer rate *	32000 Mbit/s	Power	
Interface type * Single-mode fiber (SMF) supported Multi-mode fiber (MMF) supported Fiber optic connector Maximum transfer distance Wavelength Ethernet LAN Ethernet interface type Digital Diagnostics Monitoring (DDM) Wavelength-division multiplexing (WDM)	QSFP+ ★ ✓ MPO 2000 m 1310 nm ✓ 40 Gigabit Ethernet ✓	Input voltage Maximum voltage Power consumption (typical) Operational conditions Maximum operating temperature Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Weight & dimensions	3.3 V 3.5 V 3.5 W 70 °C 0 - 70 °C -40 - 85 °C 0 - 95% 0 - 95%
Features		Width	13.5 mm
Product colour		Depth Height Weight	72.4 mm 18.4 mm 42 g
Housing material Plug and Play	Silver Metal	Height	
Housing material Plug and Play Hot-Plug support		Height	
Plug and Play		Height Weight	
Plug and Play Hot-Plug support Hot-swap		Height Weight Packaging data Number of products included	42 g 1 pc(s)



5056468775269

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.