

## Item description

PIO3 hardware configuration

- 2 x ETHERNET port for connecting to field devices and the engineering tool
- 2 x USB port for optional connection of a USB stick, mouse or keyboard
- Audio interface for connecting a headphone or loudspeaker
- CAN for controlling field devices
- 1 x RS-232/485 interface for controlling field devices with a serial interface
- 4 x digital input/output for reading/triggering digital signals
- Power-failure-proof storage component

## Data

### Technical data

Display diagonal	14.5 cm (5.7 inches)
Display	Resistive touchscreen (black front)
Display colors	262,000 colors
Graphics resolution	(640 x 480) px
Contrast ratio	300:1
Viewing angle (horizontal/vertical)	80° / 80°
Brightness	630 cd/m <sup>2</sup>
Visualization	Web server Web-Visu Target Visu
ETHERNET protocols	DHCP

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG  
 Hansastr. 27  
 32423 Minden  
 Phone: +49571 887-0 | Fax: +49571 887-169  
 Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
 We are always happy to take your call at +49 (571) 887-44222.



DNS  
FTP  
FTPS  
HTTP  
HTTPS  
SSH

Communication	<p>Web browser Web browser (HTML5) Modbus TCP master/slave Modbus (UDP), WagoAppPlcModbus Library Modbus (RTU), WagoAppPlcModbus Library ETHERNET EtherNet/IP™ Adapter (slave) EtherNet/IP™ Scanner CANopen EtherCAT® Master OPC UA Server/Client OPC UA Pub/Sub (can be installed later) MQTT RS-232 serial interface RS-485 interface BACnet/IP, <b>requires an additional license</b> Telecontrol protocols, <b>requires an additional license</b> MicroBrowser (Visualization of CODESYS V2.3), requires an additional license</p>
Operating system	Real-time Linux (with RT-Preempt patch)
Processor	ARM® Cortex® A9 Quadcore 1.0 GHz
Programming environment	CODESYS V3.5, from firmware release 24 <i>e!COCKPIT</i> (based on CODESYS V3), up to firmware release 22
Main memory (RAM)	2,048 MB
Internal memory (flash)	4096 MB
Program memory	32 MB
Data memory	128 MB
Non-volatile software memory	128. Kbytes
Type of memory card	microSD (max. 2 GB); microSDHC (max. 32 GB)
Indicators	Three-color LED (red, green, blue)
Controls	Resistive touch panel; 2 capacitive keys; proximity sensor
Supply voltage	24 VSELV DC (18 ... 31.2 V); with reverse voltage protection
Operating power	7.0 W, without USB load; 12.0 W, with USB load

## Connection data

Connection technology: communication/fieldbus

Modbus (TCP, UDP): 2 x RJ-45; EtherNet/IP™: 2 x RJ-

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG

Hansastr. 27

32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169

Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.



45; CANopen: 1 x D-sub 9 plug; Modbus (UDP): 2 x RJ-45; RS-232 + RS-485/422 serial interface: 1 x D-sub 9 socket; USB: 2 x USB 2.0 host (type A)

Connection technology: supply

1 x included female connector (734-103) with three CAGE CLAMP® connections

## Physical data

Width 172 mm / 6.772 inches

Height 163 mm / 6.417 inches

Depth 78 mm / 3.070 inches

Panel cutout (W x H) (157 x 148) mm

## Mechanical Data

Weight 0 g

## Environmental requirements

Ambient temperature (operation) -20 ... +55 °C (when mounted vertically; -20 ... +50 °C, other mounting positions)

Ambient temperature (storage) -20 ... +80 °C

Protection type IP65

Note on protection type IP65 (front side); IP20 (rear side), per EN 60529

Relative humidity (without condensation) 90 %

Mounting type Clamping elements (included) or VESA mount (4 x M4x8)

## Commercial data

ETIM 8.0 EC001414

ETIM 7.0 EC001414

PU (SPU) 1 pcs

Packaging type box

Country of origin DE

GTIN 4055143942300

Customs tariff number 84714100000

## Environmental Product Compliance

RoHS Compliance Status Compliant, No Exemption

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG

Hansastr. 27

32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169




Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?


We are always happy to take your call at +49 (571) 887-44222.

## Approvals / Certificates


### General approvals

Logo	Approval	Additional Approval Text	Certificate name
	EAC Brjansker Zertifizierungsstelle	TP TC 020/2011	EAC RU C-DE.AM02.B.00087/19
	KC National Radio Research Agency	Article 58-2, Clause 3	MSIP-REM-W43-WBP762
	UL Underwriters Laboratories Inc. (ORDINARY LOCATIONS)	UL 61010-2-201	E175199

### Declarations of conformity and manufacturer's declarations

Logo	Approval	Additional Approval Text	Certificate name
	EU-Declaration of Conformity WAGO GmbH & Co. KG	-	-

### Approvals for marine applications

Logo	Approval	Additional Approval Text	Certificate name
	DNV DNV Germany GmbH	DNV-CG-0339, Aug. 2021	TAA00001FS

## Optional accessories

### Software

#### Software applications



Item no.: 2759-208/211-1000  
Library MTP; Single License; Online activation

[www.wago.com/2759-208/211-1000](http://www.wago.com/2759-208/211-1000)

### Mounting

#### Mounting accessories

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG  
Hansastr. 27  
32423 Minden  
Phone: +49571 887-0 | Fax: +49571 887-169  
Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
We are always happy to take your call at +49 (571) 887-44222.



Item no.: 762-9001  
e!DISPLAY7300T ; Clamping elements (4 pieces)

[www.wago.com/762-9001](http://www.wago.com/762-9001)

## Memory card

Memory card



Item no.: 758-879/000-3102  
Memory Card SD Micro; 2 GByte

[www.wago.com/758-879/000-3102](http://www.wago.com/758-879/000-3102)



Item no.: 758-879/000-3108  
Memory Card SD Micro; pSLC-NAND; 8 GB; Temperature range: -40 to 90°C

[www.wago.com/758-879/000-3108](http://www.wago.com/758-879/000-3108)

## Downloads

### Documentation

#### Manual

Product Manual WAGO Touch Panel 600 Marine Line	V 1.5.0 2022 May 24	pdf 2.4 MB	Download
Migration Guide from e!COCKPIT projects to CODESYS V3.5 Online Help (HTML)		URL	Download

#### Bid Text

762-6302/8000-002 X81 - Datei		xml 6.9 kB	Download
762-6302/8000-002 docx - Datei		docx 20.0 kB	Download

#### System Description

Touch Panel 600, system description		pdf 151.9 kB	Download
-------------------------------------	--	-----------------	----------

#### Additional Information

WAGO OPC UA Server	V 1.1.0 2021 Jan 28	pdf 1.2 MB	Download
--------------------	------------------------	---------------	----------

## Application Notes

### Application Note e!COCKPIT

Subject to changes. Please also observe the further product documentation!



e!COCKPIT Anwendungshinweis HVAC BACnet Macros (a2021010) Basierend auf der Bibliothek WagoAppBuildingHVAC_BACnet stellt WAGO in dem Bereich Heizung, Lüftung und Klimatisierung verschieden HLK-Anlagenmakros mit BACnet-Anbindung zur Verfügung.	1.3.0 2023 Feb 27	zip 69.2 MB	Download
---	----------------------	----------------	----------

## Engineering-Software

### Desktop Application

WAGUpload WAGUpload is a stand-alone PC software for transferring, backing up and restoring PLC applications on WAGO 750 Series controllers.		URL	Download
---	--	-----	----------

## Runtime Software

### Firmware

Image Update (SD Karte) TP 600 WAGO_FW0762-4xxx_V031010_IX22_SP1_I	V 22 SP1 2022 Dec 14	zip 220.8 MB	Download
WUP Update (WAGUpload Tool) TP 600 WAGO_FW0762-4xxx_V031010_IX22_SP1_W	V 22 SP1 2022 Dec 14	zip 219.0 MB	Download

## CAD/CAE-Data

### CAD data

2D/3D Models 762-6302/8000-002		URL	Download
--------------------------------	--	-----	----------

### CAE data

ZUKEN Portal 762-6302/8000-002		URL	Download
EPLAN Data Portal 762-6302/8000-002		URL	Download

## Environmental Product Compliance

### Compliance Search

Environmental Product Compliance 762-6302/8000-002 Touch Panel 600; 14.5 cm (5.7"); 640 x 480 pixels; 2 x ETHERNET, 2 x USB, CAN, DI /DO, RS-232/485, Audio; Control Panel		URL	Download
---	--	-----	----------

Subject to changes. Please also observe the further product documentation!



---

## Installation Notes

## Product family

### Marine Line

[Show all products from the family](#)

Subject to changes. Please also observe the further product documentation!

---

WAGO GmbH & Co. KG

Hansastr. 27

32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169

Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.