

## Specification Sheet

Part Number: CT2012X2



Self-Laminating Tag, Caution Write-On, Telephone Cable, 3.5" x 2.0", Yellow, 25/pkg

Article Number

597-00031

Type

CT2012

Color

Yellow (YE)

### Features & Benefits

- Clear laminating plastic flap permanently protects the writing and data marked on the tag.
- Mounting holes for easy mounting using standard cable ties.
- Markers can be mounted in any direction, either vertically, horizontally, as a wrap-around identification plate or as a flag for the best visual position on the cable assembly.

Quantity Per

pack

**Product Description**

HellermannTyton's Rite-On Markers are made from a flexible vinyl film and used to mark wire and cable. The self-laminating labels have a clear tail which seals the legend under clear vinyl, maintaining the quality of the labels. The Rite-On markers are packaged in a reusable dispenser made from high impact plastic which is resistant to oils and grease. **Product Features/** - Easily and conveniently fits in a pants or shirt pocket. - Once loaded, unit allows minimal label exposure to dust and moisture. - Can be used with standard ball point pens or HellermannTyton nylon marking pens. - Excess liner is easily cut-off by tearing it over the edge guide at the front of the unit. - The dispenser can be reloaded over and over again, making it a cost-effective and efficient method of labeling.

**Short Description**

Self-Laminating Tag, Caution Write-On, Telephone Cable, 3.5" x 2.0", Yellow, 25/pkg

**Global Part Name**

CT2012-PVC-YE

**Technical Description**

Caution Write-On Self-Laminating Tag, Telephone Cable, 3.5" X 2.0", Yellow

**Width W (Imperial)**

3.5

**Width W (Metric)**

88.9

**Height H (Imperial)**

1.5

**Height H (Metric)**

38.1

**Material**

Polyvinylchloride (PVC)

**Material Shortcut**

PVC

**Adhesive**

Acrylic

**Halogen free**

No

<b>Adhesive Operating Temperature</b>	-40°F to +302°F (-40°C to +150°C)
---------------------------------------	-----------------------------------

**Operating Temperature (Metric)** -40°F to +257°F (-40°C to +125°C)

<b>Reach Complaint(Article 33)</b>	Yes
------------------------------------	-----

**ROHS Complaint** Yes

<b>Package Quantity(Imperial)</b>	25
-----------------------------------	----

**Package Quantity (Metric)** 25

<b>Customs Number</b>	3926909988
-----------------------	------------

**Content Unit(BMEcat)** pack

<b>Labels per Column</b>	1
--------------------------	---

**Labels per Row** 1

<b>Weight (Metric)</b>	0.22
------------------------	------

**Weight (Imperial)** 0.5