

## SUMMARY

### # Wires

Low voltage	10
High voltage	1



*Image is for illustrative purpose only*

Series	3P
Termination type	Male solder
IP rating	61
AWG wire size	30.00 - 22.00
Cable Ø	6.70 - 7.50 mm
Status	active

### Download

[Request a quote](#)

[Catalog](#)

## TECHNICAL DETAILS

### Mechanics

Shell Style/Model	FG*: Straight plug with key and cable seal
Keying	User configurable, 1 of 11 key positions. Plug: male contacts; Receptacle: female contacts
Housing Material	PSU (Polysulfone), gray
Weight	20.62 g

### Performance

Configuration	3P.709 : 1 High Voltage + 9 Low Voltage + 1 Ground contact
Insulator	J: PEEK/PEEK
Rated Current	4 Amps


### Others

Endurance (Shell):	>1000 mating cycles
F ret (min):	100 N
F ret (max):	200 N
Steam sterilization:	20 times (with potting on rear connection)

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

---

## DRAWINGS



### Dimensions

	A	L
mm.	21.2	63
in.	0,83	2,48

---

## RECOMMENDED BY LEMO

### Tools

Crimp settings:                   AWG/Selector = 20-22-24/6-5-5

Replacement contact:           EGG.3P.661.ZZY

### Cables

*LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.*